
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Henry Meldrum under GLO Contract Number 450, dated June 11, 1882. Surveyor General record states:

Marked a Pine 48 in. diam. ¼S on N face for ¼ Sec. Cor. from which:

A Pine 48 in. diam. bears \$3°W, 38 lks. dist. marked ½\$ BT A Fir 18 in. diam. bears N10°E, 29 lks. dist. marked ½\$ BT



No record of subsequent monumentation found in Union County survey records

## Description of corner evidence found:

Found no evidence of the original corner monument. Area has been very heavily logged.

See map of survey dated June 1992.

## Description of monument and accessories I established to perpetuate the

original location of this corner:

At the proportionate position as determined by survey [ 32 24 x30 aluminum pipe with aluminum cap marked as shown, 28 inches in the ground, I set a

New Bearing Trees; A 12 inch diameter Ponderosa Pine bears N60°E, 20.30 feet marked ¼ S21 BT A 10 inch diameter Tamarack bears S47°E, 22.65 feet marked X BT A 12 inch diameter Tamarack bears S22°W, 17.27 feet marked ¼ S28 BT A 9 inch diameter Tamarack bears N18°W, 48.11 feet marked ¼ S21 BT

Set a steel fence post approximately 5 feet East with Attention sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on May 27, 1992.

Witness: Peter Crabtree

CHIFFITA T28 R37E S 21 S 28 1992 OPLS 644

REGISTERED PROFESSIONAL AMD SIR SYOR DUANE L GRIFFITH

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of...... County of..... State of....... , I hereby certify that the within instrument was filed in this office for record on the day of by the day of (COUNTY OFFICIAL) (DEPUTY) 50+ 1 carried 9/15-192

Form R6-7100-57 (9/71)

File No. 059-1992R

\*GPO-591-971, 1988

1-8

R-11