
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

None.

T2S R37ES-13



DESCRIPTION OF CORNER EVIDENCE FOUND:

None.

SEE SURVEY NUMBER 006-2019

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At the position by survey I set a 5/8"x30" iron pin 26" in the ground with 2 ½" aluminum cap marked as shown below, from which:

NEW BEARING TREES:

A 13" Ponderosa Pine bears North 26° East a dist. of 26.15 ft., marked N 1/16 S27 BT. A 6" Ponderosa Pine bears North 49° West a dist. of 20.70 ft., marked N 1/16 S28 BT.

Set steel fence post approx. 1 ft. South

I hereby certify that the corner was monumented on April 25, 2019. Witness: Kyle A. Tucker.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
June 2, 2010
JEFFREY S. HSU
83571

Renewal Date: June 30, 2019

T2S R37E N 1/16
S28 S27

2019

OPLS 83571

UNION COUNTY
SURVEYOR

Date Received 5/14/19

Siled By 1/16/14/19

File Number 019-7019 R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 13° East declination, the distances are to a 60d spike driven into the right side of the root crown of the bearing trees. The bearings are to a brass washer marked OPLS 83571 attached to the BT blaze of the new bearing trees.