

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:


Corner originally established by John A. Hurlburt under GLO contract number 201 dated August 5, 1873. Surveyor General field notes state:

Set basalt stone 18x15x7, 8 in. in ground and made stone mound 2 ft. high for 1/4 sec. cor.

Corner verified by Henry Meldrum under GLO contract number 450 dated June 11, 1882. Surveyor General field notes states:

To a point 35 lks North of stone 1/4 sec. cor. in stone mound.

T 2 S R 37 E V-15



DESCRIPTION OF CORNER EVIDENCE FOUND:

None
 A loose 1" OD iron pipe with yellow painted top was found loose in the vicinity.

SEE SURVEY NUMBER 006-2019

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At proportionate position, I set a 2 1/2"x30" aluminum pipe 10" in the ground, with 2 1/2" aluminum cap marked as shown below, with mound of stone 2' diameter, from which:

NEW BEARING OBJECTS:

- A 5/8"x30" iron pin bears North 75°57' East a dist. of 42.21 ft., with 1 1/2" aluminum cap marked NE RP.
- A 5/8"x30" iron pin bears South 34°30' East a dist. of 58.29 ft., with 1 1/2" aluminum cap marked SE RP.
- A 5/8"x30" iron pin bears North 70°11' West a dist. of 13.57 ft., with 1 1/2" aluminum cap marked SW RP.
- A 7'x12'x5' rock outcropping bears North 3°12' West a dist. of 37.26 ft., marked X BO.

A fence corner falls approx. 200 ft South of proportionate position from which fences bears East, South, and West

I hereby certify that the corner was monumented on April 23, 2019.
 Witness: Kyle A. Tucker

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
June 2, 2010
JEFFREY S. HSU
83571

Renewal Date: June 30, 2019

BAGETT - GRIFFITH & BLACKMAN

T2S R37E

1/4 $\frac{S 27}{S 34}$

2019

OPLS 83571

**UNION COUNTY
SURVEYOR**

Date Received 4/30/19

Date Filed 4/30/19

Filed By *N. G. Blair*

File Number 018-2019R

I used a Leica GS18 RTK GPS in the establishment of the new accessories. Basis of bearing is as per Survey Number 006-2019. The distances and bearings are to the center of the aluminum caps or to the chiseled X in the rock.