


UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner was originally established by Timothy W. Davenport under GLO contract number 102, dated January 12, 1864. Surveyor General records states.

T 2 S R 38 E A-15



DESCRIPTION OF CORNER EVIDENCE FOUND:

Center line of Hunter road and fence lines running East and West.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the intersection of the centerline of Hunter Road and the projected East and West fence lines I set a 2½" x 30" Copper Clad monument with cap in a valve box marked as shown below, 30" in the ground from which:

- A 5/8" iron pin with 1/1/2" aluminum cap bears S51°W, a distance of 38.83 feet, marked UNION COUNTY SURVEY MARKER SW RP.
- A 5/8" iron pin with 1/1/2" aluminum cap bears S58°E, a distance of 32.45 feet, marked UNION COUNTY SURVEY MARKER SE RP.
- A 5/8" iron pin with 1/1/2" aluminum cap bears N55°E, a distance of 31.40 feet, marked UNION COUNTY SURVEY MARKER NE RP.
- A Power Pole with a 60d spike 0.10 off ground bears N30°W, a distance of 48.30 feet, Power Pole number #035035084.

I hereby certify that the corner was monumented on October 15, 1999.
Witness: Norbert Volny, Greg Blackman Jr.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 13, 1973
GREGORY T. BLACKMAN
991

Renewal Date: Dec. 31, 1999

UNION COUNTY SURVEYOR

T1S R38E

1/4 $\frac{S\ 34}{S\ 3}$

T 2 S
1999

OPLS 991

UNION COUNTY SURVEYOR

Date Received 10/18/99

Date Filed 1-7-2000

Filed By R. Robinson, Deputy

File Number 060-1999R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to the center of the caps on the reference pins.