


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established and monumented on Union County survey number 148-78, done by me for Dale Decker. I monumented the corner with a 5/8" x 30" iron pin with plastic cap marked BGA SURVEY MARKER. I drove a spike in an 18 inch diameter Ponderosa Pine S24°21'E, 14.28 feet, and in an 8 inch diameter Douglas Fir N83°16'W, 22.75 feet.



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found 5/8" pin with plastic cap described above.

Survey number 42-83 by William L. Hanley found the original GLO corner for the North 1/4 corner of Section 5, T2S R38E. This affected my subdivision of Section 4, as I used a proportionate position for the found Hanley corner. I amend my survey for Mr. Decker and reset the existing pin South 1.63 feet and East 5.10 feet.

See Union County Survey Number 1-90.

Description of monument and accessories I established to perpetuate the

original location of this corner: At position described above, I reset the existing 5/8"x30" iron pin with plastic cap marked BGA SURVEY MARKER, from which;


New Location of Existing Bearing Trees;
A 20 inch diameter Ponderosa Pine bears S3°58'E, 11.41 feet
A 10 inch diameter Douglas Fir bears N81°11'W, 28.03 feet

Due to private ownership of the land, trees were not scribed or painted. A 50d spike was originally driven in the face of the root crown and the bearing and distance was taken to them.

I hereby certify that the above corner point was perpetuated as hereon described on January 5, 1990.

Witnesses: Greg Blackman and Rick Robinson

UNION COUNTY SURVEYOR
File Received <u>1-19-90</u>
Filed <u>1-23-90</u>
By <u>R. Robinson, Deputy</u>
File No. <u>1-90R</u>



Duane I. Griffith



I originally used a steel tape and theodolite in the location of the accessories. I used the same basis of bearing as survey number 148-78. The new bearings and distances to the accessories were mathematically computed from the original ties. The distance and bearing is to a 50d spike driven in the face of the tree at the root crown.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)