


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner established and monumented on Union County survey number 73-78, done by me for Dr. John Vanderbilt. I monumented the corner with a 5/8" x 30" iron pin with plastic cap marked BGA SURVEY MARKER.



No record of subsequent monumentation found in Union County survey records.

**Description of corner evidence found:**

Found 5/8" pin with plastic cap described above.

Survey number 42-83 by William L. Hanley found the original GLO corner for the North 1/4 corner of Section 5, T2S R38E. This affected my subdivision of Section 4, as I used a proportionate position for the found Hanley corner. I amend my survey for Dr. Vanderbilt and reset the existing pin South 1.09 feet and East 3.41 feet.

See Union County Survey Number 1-90.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

At position described above, I reset the existing 5/8"x30" iron pin with plastic cap marked BGA SURVEY MARKER, from which;

- New Bearing Trees;**  
 A 10 inch diameter Ponderosa Pine bears N17°E, 15.75 feet  
 A 13 inch diameter Ponderosa Pine bears S27°E, 18.94 feet  
 A 7 inch diameter Ponderosa Pine bears S29°W, 19.84 feet  
 A 10 inch diameter Ponderosa Pine bears N62°W, 32.07 feet

Due to private ownership of the land, trees were not scribed or painted. A 50d spike was driven in the right side of the root crown and the bearing and distance was taken to them.

Corner position falls in an existing East-West fenceline approximately 35 feet East of an existing North-South fenceline.

I hereby certify that the above corner point was perpetuated as hereon described on January 5, 1990.

Witnesses: Greg Blackman and Rick Robinson



*[Signature]*  
 OREGON  
 JULY 10, 1984  
**DUANE I. GRIFFITH**  
 644

UNION COUNTY SURVEYOR	
Date Received	<u>1-9-90</u>
Filed	<u>1-23-90</u>
By	<u>R. ROBINSON, DEPUTY</u>
File No.	<u>2-90R</u>

I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° magnetic declination. The distances are to a 50d spike driven in the right side of the root crown.

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)