UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:


Corner originally established Herman D. Gradon, under GLO Contract No. 452, dated March 31, 1882. Surveyor General records states:

Set a post 3 ft. long 3 ins. Square 24 ins in the ground, for 1/4 Sec Cor marked 1/4S on W face, from which:

A fir 8 ins diam, bears S80°E, 12 lks dist marked 1/4S BT A tamarack 8 ins diam, bears S20°W, 8 lks dist marked 1/4S BT

Survey No. 63-79 states; Corner searched for not found. Extensive logging in this area.

Survey No. 63-79 used a proportionate position for the corner



DESCRIPTION OF CORNER EVIDENCE FOUND:

No evidence found of original corner monument or its' accessories

See Survey Number 023-2001

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position established determined by survey, I set a 2 ½" aluminum pipe with aluminum cap, 24" in the ground, marked as shown below, from which;

NEW BEARING TREES:

A 6" Ponderosa Pine bears East, 26.0 feet, marked 1/4 S8 BT.

A 10" Douglas Fir bears S51°E, 29.4 feet, marked X BT.

A 8" Ponderosa Pine bears S33°W, 25.2 feet, marked 1/4 S7 BT. A 8" Ponderosa Pine bears N41°W, 12.9 feet, marked 1/4 S7 BT.


Set steel fence post approximately 1 foot North of monument

Raised a mound of stone around monument, 3 ft. base to top of cap.

I hereby certify that the corner was monumented on June 7, 2001. Witness: Norbert W. Volny and Gregory T. Blackman Jr.

REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON RICK G. ROBINSON 2219

Renewal Date December 31, 2002



UNION COUNTY **SURVEYOR** 031-2001R File Number

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 60d spike driven into the right side of the root crown of the bearing tree. attached a brass washer marked OPLS 2219 to the BT blaze.

G-05