
CORNER REFERENCE INDEX

EXA	MPLE	
REFERENCE NO.		EXPLANATION
10 - 83	Refer	to Survey Map File
10 - 83N	Refer	to Narrative File
10 - 83R	Refer r filed	to Corner Restoration File
file no.		



REFERENCE NO.	NOTES & DESCRIPTION	
SURVEY # 3-61		VOELZ -196
Survey # 58-77	FOUND 34" PIPE .85' WEST - SET AT COR	
	A 1" x 36" PIPE W/B.C.	GRIFFITH - 1977
Survey # 62-78	FOUND MON OF RECORD	GRIFFMY-1978
Survey # 54-81	FOUND MONUMENT OF RECORD	GRIFFITH-1981
SURVEY# 14-84	FO BRASS CAP SET BY SURVEY #58-77	BLACKMAN-1984
850 - 84R	MOHUMENTATION RECORD	BLACKMAN-198

		· · · · · · · · · · · · · · · · · · ·
		_

CORNER LOCATION CODE N-11

History	of	original	comer	establishment:
---------	----	----------	-------	----------------

Corner originally established by David T. Thompson under GLO contract number 103, dated September 3, 1863. Surveyor General record states:

Set post for $\mbox{$4$}$ Sec corner in mound of earth with pits, trench, charred stake as per instructions

Corner monumented by survey number 58-77 by Duane I. Griffith, who set a 1 inch x 36 inch pipe with brass cap marked as shown

DI	AGRAI	И
	T2S	R38E
٦.	s	16
	S	21

Description of corner evidence found:


Found brass cap monument as per survey number 58-77

Description of monument and accessories I established to perpetuate the original location of this corner:

NONE

See survey number 14-84





Office of Cour	nty of		
State of , I hereby certify that the	within instrument was filed	in this office	
for record on the day of by	. <i>, 19</i>	UNION CO	YTMUC
(COUNTY OFFICIAL)	(DEPUTY)	SURVE	OK

Form R6-7100-57 (9/71)

Date Filed 4-26-84

By G. LANGLITZ, DEPUTY

File No. 850-84 R

HORIZONTAL CONTROL DATA

UNION COUNTY, OREGON **OREGON STATE PLANE, NORTH ZONE (3601)**

STA NAME:

2018015

1/4 SECTION CORNER COMMON TO SECTIONS 16 AND 21

TWP.

2 S

RGE.

38 E.

GEODETIC COORD: NAD 83(91)

DATE TIED: January 30, 2018

LAT:

45 ° 23 '

2.49164 " N

SURVEYOR: RICK G. ROBINSON

OPLS 2219

LONG:

118° 3'

57.27127 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN

2006 ADAMS AVENUE

LAGRANDE, OR 97850

(541) 963-6092

SP. COOR: NAD 83(91)

N: 635522.694

INT FT.

E:

8827383.363

INT FT.

TYPE: GPS

THETA:

1 ° 43 ' 34.4046825 "

ORDER: SECOND CLASS: 1

SCALE FACTOR:

0.9999016274

ELEV:

2780.28

US FT.

ELEV: DATUM: NGVD 29

COMMENTS:

1" Iron pipe with 2 1/2" brass cap marked as shown.

T2S R38E S 16

S 21

OPLS 644

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON July 17, 1986

RICK G. ROBINSON

2219

Renewal Date: December 31, 2018

1 METER = 3.2808333333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)