CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established in 1863 by D. P. Thompson under Contract No. 103.

Set post in mound of earth with charred stake pits trench.

DIAGRAM

COR T2S R39E _S7 |S8 S18 |S17 ORE LIC 381 1970

Description of corner evidence found:

Found 3° Brass cap on 2 3/8" iron pipe buried 18 inches below the surface with a stone along the west side. Cap is stamped as shown in diagram above.

Description of monument and accessories l'established to perpetuate the original location of this corner:

None

I hereby certify the above corner was found and described by me on April 20, 1986.

UNION COUNTY SURVEYOR
Data Received 5-1-86
Date Filed 5-2-86
BY G. LANGLITZ DEPUTY
File No. 24-86 R
SEE SURVEY 16-86

P.F.	REGISTERED ROFFICEIONAL A STATE OF THE STATE	
	OREGON JULY 13, 1979 B. A. SUTTON 1 8 4 8	

Office of	County of
State of, / hereby	y certify that the within instrument was filed in this office
for record on the day of	, 19
***************************************	by
(COUNTY OFFICIAL)	(DEPUTY)

HORIZONTAL CONTROL DATA

UNION COUNTY, OREGON OREGON STATE PLANE, NORTH ZONE (3601)

STA NAME:

200701

SECTION CORNER COMMON TO SECTIONS: 7, 8, 17 and 18

TWP.

2 S. RGE. 39 Ε. GEODETIC COORD: NAD 83(91)

DATE TIED: Feb. 7, 2007

LAT:

45 ° 23 '

55.50159 " N

SURVEYOR: RICK G. ROBINSON

OPLS 2219

LONG:

117° 58'

24.78405 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN

2006 ADAMS AVENUE

LAGRANDE, OR 97850

(541) 963-6092

SP. COOR: NAD 83(91)

N:

641617.086

INT FT.

8850933.262 E:

INT FT.

TYPE: GPS

THETA:

47 ' 30.1999698 "

ORDER: SECOND CLASS: 1

SCALE FACTOR:

0.9999026247

ELEV:


2751.08

US FT.

ELEV: DATUM: NGVD 29

COMMENTS:

Corner is 2" iron pipe 1 ft. below the ground with 3" brass cap marked as shown:



REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON RICK G. ROBINSON 2219

Renewal Date: December 31, 2008

1 METER = 3.2808333333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)