


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history.



Description of corner evidence found:

No evidence found.

Description of monument and accessories | established to perpetuate the original location of this corner:

I se a brass cap on a 1 in. x 30 in. galvanized iron pipe set within 4 in. of the surface, from which I set two bearing trees:

A Douglas Fir 6 in. dia. bears N 58 32 W, 17.90 feet (Horiz. dist.) and being scribed E 1/16 S 32 BT.

A Douglas Fir 15 in. dia. bears S 23 19 W, 23.10 feet (Horiz. dist.) and being scribed E 1/16 S 5 BT.

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>12-12-86</u>
Date Filed	<u>12-22-86</u>
By	<u>G. LANGLITZ DEPUTY</u>
File No.	<u>318-86 R</u>

SEE SURVEY 37-86

REGISTERED PROFESSIONAL LAND SURVEYOR	
<i>James H. Hambleton</i>	
<u>12-10-86</u>	
OREGON JULY 10, 1984	
JAMES H. HAMBLETON 645	

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)