

Form 5000-4
(December 1979)
Revised 5100-4

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

R628

23

FIELD NOTES

OF THE

RECORDS OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 1 SOUTH, RANGE 40 EAST,

INDEX DIAGRAM

UNION COUNTY
SURVEYOR

Date Received 9-19-84

Date Filed 9-26-84

By G. LANGLITZ, DEPUTY

File No. 242-84

SHEET 1/2

REFER TO UNION CO. SURVEYOR MICROFILM RECORDS - THIS RADE FOR N

Of the WILLAMETTE Meridian

In the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 1979, approved July 17, 1979

Number 1000, which provided for the surveys included under 44-B-Survey/Comp
and assignment instructions dated July 30, 1982.

Survey commenced September 15, 1982

Survey completed September 17, 1982

...bearing...
...magnetic declination is 20° E.

The monumentation of original corner posts was made at the request of the United States Forest Service, in conjunction with their Land Relocation Program.
The magnetic declination is 20° E.

South Boundary, T. 1 S., R. 40 E.,
Willamette Meridian, Oregon

(Reconvening corners established by Henry Waldron,
Deputy Surveyor, No. 3033)

The corner of sec. 1 and 16, on the S. by. of the T. 1 S. determined from the bearing and distance from the original bearing trees:

A large oak, 15 inch diam., bears S. 34° E., 15 lbs. dist., with scribble marks & S NE visible on stump base (marked 44 lbs.)

A large oak, 11 inch diam., bears N. 40° W., 2 lbs. dist., with scribble marks & S NE visible on stump base

At the corner point
Set an aluminum post, 30 inch long, 7/8 inch diam., 17 inch in the ground, in a hole 3 inch dia. and 2 inch deep, with a mound of stone, 3 ft. base, to top, with aluminum cap and...

(...)

...
from which the bearing trees...

A fir, 12 inch diam., bears N. 74° E., 49 lbs. dist., with...

A fir, 15 inch diam., bears S. 20° W., 22 1/2 lbs. dist., with...

Corner is located 3 lbs. N. of a wire fence, extending E. and W.

The cor. of sec. 4, 5, 11, and 19, on the S. by. of the T. 1 S. determined from the bearing and distance from the remains of the original bearing trees:

A stump base, bears N. 45° E., 30 lbs. dist., with a down pine stump, 12 inch diam., with scribble marks...

UNION COUNTY SURVEYOR
Date Received 9-19-84
Date Filed 9-26-84
By G. LANGLITZ, DEPUTY
File No. 942-8A

SHEET 2/2

T. 1 S., R. 40 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, Township 1 South, Range 40 East, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group No. 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories When Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

South Boundary, T. 1 S., R. 40 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Henry Meldrum,
U. S. Deputy Surveyor, in 1882)

The 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., determined from the remains of the original bearing trees:

A larch snag, 16 ins. diam., bears S. 34° E., 15 lks. dist., with scribe marks 1/2 S BT visible on opened blaze. (Record, 14 lks.)

A larch snag, 11 ins. diam., bears N. 40° W., 2 lks. dist., with scribe marks 1/2 S BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 1 S R 40 E
1/4 S 36
S 1
T 2 S
1982

from which new bearing trees

A fir, 12 ins. diam., bears N. 74° E., 49 lks. dist., mkd. 1/2 S36 BT.

A fir, 15 ins. diam., bears S. 2° W., 22 1/2 lks. dist., mkd. 1/2 S1 BT.

Corner is located 3 lks. N. of a wire fence, extending E. and W.

~~The cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:~~

~~A stump hole, bears N. 62° E., 30 lks. dist., with a down pine alongside, 12 ins. diam., with scribe marks S36 BT visible on open blaze.~~

UNION COUNTY SURVEYOR	
Date Received	4/9/15
Date Filed	4/9/15
By	<i>W. G. Gibson</i>
File No.	087-2015R