CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Henry Meldrum under GLO Contract No. 450 and dated June 11, 1882.

Surveyor General records state:

Set post 4 ft long 4 in square 24 in in ground for Corto Secs 1,2,11 & 12 marked T2SS11 on SW, R40ES2 on NW, Sl on NE, Sl2 on SE with 5 notches on S and 1 on E edge from which:

	E-21		
	DIAGRAM		
	T 2 S	R 40 E	
	S 2	S 1	
r	S 11	S 12	
'	1988		
	ORLS	1639	

A tamarack 6 in diam bears S31°W, 4 lks dist marked T2SS11 BT. A fir 11 in diam bears N46°W, 37 lks dist marked R40ES2 BT. A pine 10 in diam bears N43°E, 8 lks dist marked S1 BT. A pine 10 in diam bears S65°E, 9 lks dist marked S12 BT.

Description of corner evidence found:

Found a rotten root hole flush with ground surface for sections 1,11 & 12 BT's at record positions.

A sawed red fir stump 2' high and 35" diam with "T" scribe and chaining notch inside 9" overgrowth opened this date from which remains of rotten post brs $546^{\circ}E$, 37 lks dist per record.

UNION COUNTY SURVEYOR Date Received 9-22-88 File No. 137-88 R

Description of monument and accessories I established to perpetuate the original location of this corner:

At position of recovered wood post remains...

Set $2\frac{1}{2}$ aluminum cap on 2" aluminum pipe 24" in ground & projecting out of ground with surrounding earth mound & 6' fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram.

New bearing trees established: A spruce 14" diam brs $N29\frac{1}{2}^{\circ}E$, 18.3' dist mkd T2SR40ES1 BT. A white fir 9" diam brs S29°E, 8.5' dist mkd T2SR40ES12 BT. A red fir 20" diam brs S39°W, 17.3' dist mkd T2SR40ES11 BT. A western larch 12" diam brs N37°W, 69.4' dist mkd T2SR40ES2 BT.

Each BT has a sign 54-3 & 54-9 attached below a 6" band of red paint, and each new BT has a brass washer marked PLS 1639 nailed flush with BT blaze.

Compass declination 200 East.

I hereby certify that the above described corner monument was properly remonumented by me and witnessed by Bill Gohring on July 15, 1988.

REGISTERED PROFESSIONAL LAND SURVEYOR	·
William L. Har	ley
OREGON JULY 14, 1978 WILLIAM L. HANLEY 1639	1

Office of County Surveyor	County of Union
State of O.r.eg.an , I hereby certify the	nt the within instrument was filed in this office
for record on the day of	, 19
by	***************************************
(COUNTY OFFICIAL)	(DEPLITY)