
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Henry Meldrum under GLO Contract no. 450 dated June 11, 1882, and his record states:

Set post 3 ft long 3 ins square 24 ins in ground for 1/4 Sec Cor. marked 1/4 S on N face, from which:

A pine 16 ins diam bears N50 $^{\circ}$ W, 32 lks dist marked 1/4 S BT. A fir 10 ins diam bears S10 $^{\circ}$ E, 26 lks dist marked 1/4 S BT.



Description of corner evidence found:

None. Corner reestablished by proportionate measurement from survey control.

Corner position obliterated by Forest Service logging operation.

Description of monument and accessories I established to perpetuate the original location of this corner:

At position midway between adjacent section corners east and west...

Set a 2" x 30" aluminum pipe with 2½" aluminum cap 22" in ground & projecting 8" out of ground with surrounding stone mound & placed 6' steel fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram.

New bearing trees established: White fir 10" dia brs N78 $^{\circ}$ E, 18.2' dist mkd 1/4 S14 BT. White fir 11" dia brs S25 $^{\circ}$ W, 19.0' dist mkd 1/4 S23 BT.

New bearing trees have a brass washer marked PLS 1639 nailed flush to face of blaze. Attached signs 54-3 & 54-9 & painted face of blaze & a 6' band of red around each bearing tree.

Compass declination 190 East.

I hereby certify that the above described corner monument was properly established by me & witnessed by F.S. Munro on September 26, 1989.

REGISTERED **PROFESSIONAL** LAND SURVEYOR William L. Honky OREGON JULY 14, 1978 WILLIAM L. HANLEY <u> 1639</u>

Office of County Surveyor	. County of Unic	n
Oregon , I hereby certify t	het the within instru	ment was filed in this office
for record on the day of	, 19	VINUOD NCINU
(COUNTY OFFICIAL)	anges.	(DEPUTY)
Form R6-7100-57 (9/71)	D	ate Received <u>3-12-90</u>
		into Filed 3-17-90

*GPO-591-971, 1988