


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

P-25

History of original corner establishment:

Corner originally ESTABLISHED by Henry Meldrum under GLO contract No.450 and dated June 11,1882.

Surveyor General records state: Set post 3 ft long 3 in square 24 in in ground for 1/4 Sec Cor marked 1/4S on N face, from which: A fir 12 in diam bears S49°E, 8 lks dist marked 1/4S BT. A fir 10 in diam bears S65°W, 7 lks dist marked 1/4S BT.



Corner REESTABLISHED by Alonzo Gesner under GLO contract No.683 dated June 7, 1898, during his resurvey of the east boundary of T.2S.,R.40E.,W.M... Post and bearing trees destroyed by forest fires...Set fir post 4 ft long 4 in square 24 inches in the ground marked 1/4S on the W face, from which: A fir 8 in diam bears N33°E,40 lks dist marked 1/4S BT. A fir 20 in diam bears N25°W, 142 lks dist marked 1/4S BT.

Description of corner evidence found:

Searched 8 man-hours total on 6-09-88, 8-05-88 & 8-16-88 in old burn area - original corner or accessories not found and corner declared lost.

UNION COUNTY SURVEYOR	
Received	<u>6-8-89</u>
Filed	<u>6-9-89</u>
By	<u>G. LANGRITZ, DEPUTY</u>
File No.	<u>117-89 R</u>

Description of monument and accessories established to perpetuate the original location of this corner:

At proportioned position on line between NE & SE corners to Section 24...

Set 2 1/2" aluminum cap on 2" x 30" aluminum pipe 24" in ground to bedrock & surrounded with mound of earth & stone. Set 6' steel fence post alongside corner with sign 54-9 attached. Cap marked as shown in corner diagram.

New bearing trees established:

A western larch 17" diam brs West, 29.1' dist mkd 1/4S24 BT.
A spruce 11" diam brs S33 1/2°W, 27.0' dist mkd 1/4S24 BT.

New bearing trees have a brass washer stamped PLS 1639 nailed to face of blaze. Attached signs 54-3 & 54-9 and painted face of blaze and 6" band of red around each BT.

Compass declination 19° East.

I hereby certify that the above corner monument was properly REESTABLISHED to U.S.F.S. standards by me on August 16, 1988 and witnessed by Jim DeMastus.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William D. Hanley

OREGON
JULY 14, 1978
WILLIAM I. HANLEY
1639

Office of.....County Surveyor..... County of.....Union.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)