## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:

Corner originally established by Henry Meldrum under Contract No. 450 and dated June 11, 1882.

Surveyor General records state:

Set post 4' long 4" suqare 24" in ground for Cor to Secs 23, 24, 25 & 26 marked T2SS24 on NE, R40ES23 on NW, S26 on SW and S25 on SE with 2 notches on S and 1 on E edges from which:

A fir 18" dia brs  $N59^{\circ}E$ , 47 lks dist mkd T2SS24 BT. A fir 9" dia brs  $N38^{\circ}W$ , 17 lks dist mkd R40ES23 BT. A fir 4" dia brs  $S38^{\circ}W$ , 20 lks dist mkd S26 BT. A fir 6" dia brs  $S33^{\circ}E$ , 22 lks dist mkd S25 BT.

R-21	
DIAGRAM T 2 S R 40 E	
S 23	S 24
S 26	S 25
1987	
URLS	1639

## Description of corner evidence found:

No trace of original wood post.

A sawed fir stump 28" dia with 4' long butt alongside, blaze on stump inside 10" overgrowth shows axe marks, blaze on long butt inside 10" overgrowth mkd "S25BT" on double blaze brs S33°E, 14.5' per record from reestablished corner point. No scribes or axe work identified on other sawed or standing fir trees in area.

## Description of monument and accessories I established to perpetuate the original location of this corner:

At position established by reversed record bearing and distance from sawed section 25 BT stump...

Set 2 " aluminum pipe with  $2\frac{1}{2}$  " aluminum cap 25" in the ground and surrounded with a mound of earth and stone. Cap marked as shown in corner diagram.

New bearing trees established:
A white fir 14"dia brs N80°E, 63.6' dist mkd T2SR40ES24 BT.
A white fir 16" dia brs S51°E, 22.3' dist mkd T2SR40ES25 BT.
A white fir 12" dia brs S69°W, 26.9' dist mkd T2SR40ES26 BT.
A spruce 15" dia brs N55°W, 40.6' dist mkd T2SR40ES23 BT.

New bearing trees have a brass washer stamped PLS 1639 nailed to face of blaze. Attached signs 54-3 and 54-9, painted face of blaze and 6" band of red around each BT. Set steel fence post alongside with sign 54-9 attached.

Compass declination 190 East.

I hereby certify that the above corner monument was properly remonumented to U.S.F.S. standards by me on September 16, 1987.

REGISTERED **PROFESSIONAL** LAND SURVEYOR

K. Harley

OREGON JULY 14, 1978 WILLIAM L. HANLEY

1639

Office of County Surveyor County of Union State of Oregon ... I hereby certify that the within instrument was filed in this office for record on the...... day of...... , 19..... ...... by ......

(COUNTY OFFICIAL)

William

Form R6-7100-57 (9/71)

UNION COUNTY SURVEYOR

Date Received 9-22-88 Date Filed 9-23-88

File No. 140-88 R