## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:

Corner established by Henry Meldrum under GLO Contract no. 450 dated June 11, 1882, and his record states:

Set post 4 ft long 4 ins square 24 ins in ground for Cor. of Sec. 24, 25, 35 & 36 marked T2SS 25 on NE, R40ES26 on NW, S35 on SW and S36 on SE with 1 notch on S and E edges, from which:

A fir 12 ins diam bears N22°W, 50 lks dist marked R40ES26 BT. A fir 7 ins diam bears N72°E, 75 lks dist marked T2SS24 BT. A fir 10 ins diam bears S48°E, 64 lks dist marked S36 BT.

A fir 16 ins diam bears S16°W, 85 lks dist marked S34 BT.

V-21	
DIAGRAM	
T 2 S	R 40 E
S 26	S 25
S 35	S 36
1989	
ORLS	1639

## Description of corner evidence found:

None. Corner reestablished by proportionate measurement from survey control.

Corner position is in old burn area covered heavely with alder brush.

## Description of monument and accessories I established to perpetuate the original location of this corner:

At position determined from recovered controlling adjacent section corners N, S & E and recovered 1/4 section corner 1/2 mile West... Set a 2" x 30" aluminum pipe with  $2\frac{1}{2}$ " aluminum cap 24" in ground & projecting 6" out of ground with surrounding earth mound & placed 6' steel fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram. No stones available for mound.

New bearing trees established:
Lodgepole pine 9" dia brs N06½°E, 29.7' dist mkd T2SR40ES25 BT.
Lodgepole pine 10" dia brs S30°E, 23.2' dist mkd T2SR40ES36 BT.
Lodgepole pine 8" dia brs S75½°W, 5.0' dist mkd T2SR40ES35 BT. Lodgepole pine 12" dia brs  $N51\frac{1}{2}^{O}W$ , 16.9' dist mkd T2SR40ES26 BT.

New bearing trees have a brass washer marked PLS 1639 nailed flush to face of blaze. Attached signs 54-3 & 54-9 and painted face of blaze and a 6" band of red around each bearing tree.

Compass declination 190 East.

I hereby certify that the above described corner monument was properly established by me & witnessed by F.S. Munro on September 17, 1989.

REGISTERED PROFESSIONAL LAND SURVEYOR

> OREGON WILLIAM L. HANLEY

William L. Harley

Office of County Surveyor County of Un  State of Oregon , I hereby certify that the within inst	rument was filed in this office
for record on the day of 19	
(COUNTY OFFICIAL)	(DEPUTY)

Form R6-7100-57 (9/71)

\*GPO--591-971, 1988

11-21