CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Henry Meldrum under GLO contract No. 450 and dated June 11, 1882. Surveyor General records state: Set post 3' long 3" square 24" in ground for 1/4 Sec Cor mkd 1/4S on W face from which: Pine 10" dia brs N69°E,26 lks dist mkd 1/4S BT.Pine 15" dia brs N27°W,75 lks dist mkd 1/4S BT.

X-25

DIAGRAM
T 2 S
R 40 E R 41 E
1 S 36

1987
ORLS 1639

UNION COUNTY

Data Received 8-12-87

Corner reestablished by Alonzo Gesner under contract No. 683 and dated June 7, 1898.

Surveyor General records state: Found original post marked as per record and a badly decayed 10" pine brs N69°E, 26 lks dist mkd 1/4S BT. No trace of other BT. Mkd A pine 6" dia brs S34°30'E, 18 lks dist mkd 1/4S BT. A pine 7" dia brs N69°W, 14 lks dist mkd 1/4S BT.

Description of corner evidence found:

Found rotten remains of wood post to a depth of 18" from which: A L.P. pine 12 dia brs N66 W, 9.1'(record, N69 W, 14 lks) with fragmentary scribes on partially healed blaze. A L.P. pine windblow 8" dia & root hole brs S30 E, 12.2' (record, S34½ E,18 lks) with full scribes on partially healed blaze. No trace of original BTs by Meldrum.

Description of monument and accessories I established to perpetuate the original location of this corner:

At position of found rotten remains of original post...

Set $2\frac{1}{2}$ " aluminum cap on 2" aluminum pipe 25" in ground with 5" projecting out of ground with surrounding rock mound and 6' fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram.

New bearing tree established: A L.P. pine 9" dia brs $S02^{O}W$, 15.5' dist mkd 1/4S36 BT.

Each BT has a sign 54-3 and signs 54-4 or 54-9 attached below a 6" band of red paint, and each new BT has a brass washer marked PLS 1639 nailed flush with BT blaze.

Compass declination 190 East.

I hereby certify that the above described corner monument was properly remonumented by me and witnessed by Jim DeMastus on July 16, 1987.

fin DeMastre

PROFESSIONAL LAND SURVEYOR

> OREGON JULY 14, 1978 WILLIAM L. HANLEY 1639

Office of	County Surveyor	County of Union
State ofOregon , I hereby certify that the within instrument was filed in this office		
for record on the day of , 19		
by		
	(COUNTY OFFICIAL)	(DEPUTY)