


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: A. GENSNER, 1898, CONTRACT NO. 683

40.00 SET BASALT STONE 14X11X8 INS 9 INS IN THE GROUND ON A HILLSIDE SLOPING E FOR 1/4 SEC. COR. MARKED 1/4 ON THE W. SIDE, FROM WHICH:



- A TAMARACK, 24 INS. DIAM., BEARS S.13°E., 40 LKS. DIST. MKD. 1/4 S16BT
- A WHITE FIR, 5 INS. DIAM., BEARS S.1°W., 12 LKS. DIST. MKD. 1/4 S17 BT

Description of corner evidence found:

FOUND A 12"X10"X6" [14"X11"X8"] MARKED STONE, FROM WHICH:

- A TAMARACK, 42" IN DIAM., BEARS S.11°16'E., 27.23', PARTIAL SCRIBING VISIBLE " 1/4 S16 BT"

Description of monument and accessories I established to perpetuate the original location of this corner:

SET A 3 1/4" ALUMINUM CAPPED MONUMENT 18" IN THE GROUND, WITH MOUND OF STONE TO CAP, CAP MARKED PER DIAGRAM, FROM WHICH:

- A FIR, 11" IN DIAM. BEARS N.77°17'E., 22.40', SCRIBED "1/4S16 BT".
- A FIR, 9" IN DIAM. BEARS S.81°00'W., 9.25', SCRIBED "1/4S17 BT".
- A FIR, 10" IN DIAM. BEARS N.02°21'W., 11.30', SCRIBED "BT".

REFERENCE: RECORD OF SURVEY, CLARK CREEK/EAGLE CAP WILDERNESS SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARINGS WAS A SOLAR OBSERVATION.

REGISTERED PROFESSIONAL LAND SURVEYOR

RM & Stoll 9/98

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____

_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

B

RECEIVED
 Date Received 10/28/98
 Date Filed 3/3/99
 By R. Robinson, Deputy
 File No. 004-1999R