


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Alonzo Gesner under GLO contract No. 683 and dated June 7, 1898.

Surveyor General records state:

Set fir post 4 ft long 4 ins square 24 ins in ground at the point of intersection for closing corners to Secs 19 and 30 marked CCT2SR41ES19 on the N and S30 on the S faces with 2 groves on the S and 4 groves on the W side, from which A spruce 8 in dia brs N71°30'E, 22 lks dist marked T2SR41ES19CC BT. A spruce 10 in dia brs S58°E, 45 lks dist marked T2SR41ES30CC BT.



Description of corner evidence found:

A rotten wood post remains to a depth of 15" from which:

A rotten windblow and root stub with fragmentary scribes on rotten face brs N71½°E, 22 lks dist per record.

A spruce snag 14" dia with healed double blaze brs S58°E, 45 lks dist per record.

UNION COUNTY SURVEYOR	
Date Received	<u>9-1-87</u>
Date Filed	<u>9-16-87</u>
By	<u>G. LAUGLITZ, DEPUTY</u>
File No.	<u>100-87 R</u>

Description of monument and accessories established to perpetuate the original location of this corner:

At position of rotten post remains...

Set 2½" aluminum cap on 2" aluminum pipe 25" in ground & 5" projecting out of ground with surrounding earth mound & 6' fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram.

New bearing trees established:

A 15" spruce brs N73°E, 23.6' dist mkd T2SR41ES19CC BT.

A 13" white fir brs S60°E, 30.4' dist mkd T2SR41ES30CC BT.

Each BT has a sign 54-3 and signs 54-4 or 54-9 attached below a 6" band of red paint, and each new BT has a brass washer marked PLS 1639 nailed flush with BT blaze.

Compass declination 17° East.

I hereby certify that the above described corner monument was properly remonumented by me and witnessed by Jim DeMastus on August 10, 1987.

Jim DeMastus

REGISTERED PROFESSIONAL LAND SURVEYOR

William L. Hanley

**OREGON
JULY 14, 1978
WILLIAM L. HANLEY
1639**

Office of.....County Surveyor..... County of.....Union.....
State of.....Oregon..... I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)