

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


Z-1

**History of original corner establishment:**

Corner established by Alonzo Gesner under GLO contract No. 683 and dated June 7, 1898.

Surveyor General records state: Set fir post 4' long 4" square 24" in ground for closing Cor to Townships 2 & 3 SR41E mkd CCR41E on E, T2SS31 on N and T3SSE on S faces with 6 groves on NE and S sides from which:

Pine 9" dia brs N65°E, 15 lks dist mkd T2SR41ES31 BT.  
Pine 6" dia brs S73°E, 26 lks dist mkd T3SR41ES6 BT.



**Description of corner evidence found:**

Rotten post remains to a depth of 18" from which:

A L.P. pine snag 12" dia brs N70½°E, 9.9' (record, N65°E, 15 lks) marked "CCT2SR41ES31 BT" on open blaze.

A L.P. pine snag 7" dia brs S68½°E, 17.2' (record, S73°E, 26 lks) with fragmentary scribes on open and rotting blaze.

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>8-12-87</u>
Date Filed	<u>8-24-87</u>
By	<u>G. LANGLITZ DEPUTY</u>
File No.	<u>59-87R</u>

**Description of monument and accessories I established to perpetuate the original location of this corner:**

At position of found rotten wood post...

Set 2½" aluminum cap on 2" aluminum pipe 25" in ground with 5" projecting out of ground with surrounding rock mound and 6' fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram.

New bearing trees established:

A spruce 8" dia brs N69°E, 22.2' dist mkd T2SR41ES31CC BT.

A L.P. pine 8" dia brs S54°E, 11.5' dist mkd T3SR41ES6CC BT.

Each BT has a sign 54-3 and signs 54-4 or 54-9 attached below a 6" band of red paint, and each new BT has a brass washer marked PLS 1639 nailed flush with BT blaze.

Compass declination 19° East.

I hereby certify that the above described corner monument was properly remonumented by me and witnessed by Jim DeMastus on July 16, 1987.

*Jim DeMastus*

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*William L. Hanley*

**OREGON  
JULY 14, 1978  
WILLIAM L. HANLEY  
1639**

Office of.....County Surveyor..... County of...Unity.....  
State of.....Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)