

Dependent Resurvey of Part of Subdivisions of
T. 4 N., R. 38 E.

Chains

Soil, sandy and rocky loam; 2nd and 3rd rate.
Timber, fir, pine, spruce, and tamarack.
Undergrowth, alder, willow, vinemaple, and huckleberry.

Retracement of 3 Subdivision $\frac{1}{2}$ Miles in T. 3 N., R. 38 E.

"Correction of the Survey executed by John W. Kimbrell,
Deputy Surveyor, in 1903."

The $\frac{1}{2}$ sec. cor. of secs. 3 and 4, is the rotten remains of
old stake bearing traces of incomplete scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with the marked stake deposited at the base, for
 $\frac{1}{2}$ sec. cor., with brass cap marked

$\frac{1}{2}$
S 4 | S 3
1939

from which

A pine, 14 ins. diam., bears N. 64° E., 78 lks. dist.,
marks grown over. (Old B. T.)

A pine, 10 ins. diam., bears N. 28° W., 22 lks. dist.,
marks grown over. (Old B. T.)

Thence

N. 0° 02' W., on true line bet. secs. 3 and 4.

Desc. 567 ft. over NE. slope, through heavy timber and
dense undergrowth.

29.95 Intersect S. bdy. of T. 4 N., R. 38 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the
ground, for closing cor. of secs. 3 and 4, with brass
cap marked

T4NR38E
S34
S 4 | S 3
T3N R38E
C C
1939

from which

A spruce, 16 ins. diam., bears S. 89° E., 18 lks. dist.,
marked T 3 N R 38 E S 3 C C B T. (Old B. T.)

A fir, 16 ins. diam., bears S. 57 $\frac{1}{2}$ ° W., 70 lks. dist.,
marked T 3 N R 38 E S 4 C C B T. (Old B. T.)

From point of intersection the $\frac{1}{2}$ sec. cor. of sec. 34 only,
bears N. 89° 10' E., 3.45 chs. dist., heretofore described.

30.13 The original closing cor. of secs. 3 and 4, which is a
spruce stump, 20 ins. diam., marked with 3 notches on E.
and W. sides, and T. 3 N R 38 E on S. side.

from which

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By J. M. & G. DEATH

File No. 299-2013R

Retracement of 3 Subdivision $\frac{1}{2}$ Miles in T. 3 N., R. 36 E.

Corners

A spruce, 16 ins. diam., bears S.45°E., 25 lks. dist., marked T 3 N R 36 E S 3 C C B T. (Old B. T.)

A fir, 16 ins. diam., bears S.51°W., 33 lks. dist., marked T 3 N R 36 E S 4 C C B T. (Old B. T.)

I obliterate the marks on this tree cor. stump and leave the two bearing trees intact for accessories to the new closing cor. of secs. 3 and 4, heretofore described.

Land, mountainous.

Soil, rocky loam; 3rd rate.

Timber, fir, pine, spruce, and tamarack.

Undergrowth, alder, vinemaple, willow, and huckleberry.

The $\frac{1}{2}$ sec. cor. of secs. 4 and 5, is the rotten remains of old post, 3 ft. long, 3 ins. diam., lying on the ground with stub of post still in the ground, marked $\frac{1}{2}$ S.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the marked stake deposited at the base, for $\frac{1}{2}$ sec. cor., with brass cap marked

S 5 | S 4

1939

from which

A pine, 10 ins. diam., bears S.48°E., 26 lks. dist., marked $\frac{1}{2}$ S 4 B T. (Old B. T.)

A dead and fallen pine, 4 ins. diam., bears S.23°W., 28 lks. dist., marked $\frac{1}{2}$ S 5 B T. (Old B. T.)

A pine, 6 ins. diam., bears S.62 $\frac{1}{2}$ °W., 7 lks. dist., marked $\frac{1}{2}$ S 5 B T. (New B. T.)

Thence

N.0°17'W., on true line bet. secs. 4 and 5.

Desc. 158 ft. over gradual NE. slope, through heavy timber and dense undergrowth.

29.00 Highway, (Elgin to Tollgate), bears N.30°W. and S.30°E.

29.30 The original closing cor. of secs. 4 and 5, which has been perpetuated with a galvanized iron pipe, 3 ft. long, 1 in. diam., with no marks. from which

A fir, 20 ins. diam., bears S.1°E., 6 lks. dist., marked T 3 N R 36 E S 4 C C B T. Obliterate marks. (Old B. T.)

A fir, 18 ins. diam., bears S.62 $\frac{1}{2}$ °W., 5 lks. dist., marked T 3 N R 36 E S 5 C C B T. Obliterate marks. (Old B. T.)

29.98 Intersect S. bdy. of T. 4 N., R. 36 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap marked

**UNION COUNTY
SURVEYOR**

Date Received 3/15/13

Date Filed 3/15/13

By M. & L. DEPUTY

File No. 299-2013R