

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


J-13

History of original corner establishment:

1899, John W. Kimbrell, U.S. Deputy Surveyor, working under G.L.O. contract No. 700, established this corner by setting a 28" X 20" X 12" basalt stone and marking 4 Bearing Trees. THIS WORK IS REJECTED BY THE G.L.O.

1901, John W. Kimbrell obliterates his 1899 corner and established the corner by marking a 3" diameter fir as the corner and marking 4 bearing trees. The 1899 obliterated corner bears N. 31° W., 140 links. THIS WORK IS REJECTED BY THE G.L.O.

1903, John W. Kimbrell obliterates his 1901 corner and established the corner by setting a granite stone 18 X 8 X 7 inches, 12 inches in the ground, marked with 4 notches on the South and 2 notches on the East edges, and raised a mound of stone 2 foot base by 1 1/2 feet high West of the corner. The 1901 obliterated corner bears North, 451 links.



Description of corner evidence found:

I found at the corner point a stone 18" X 8" X 7" with notches on one edge just down hill of a large stone mound.

In addition I found remnants of the 1901 (SW bearing tree a downed 30" fir) and 1899 (a stone 28" X 20" X 12" well marked set in place and the NW bearing tree, a 24" fir with healed blaze) obliterated corners. From corner point the 1899 corner (N. 7 1/4° W., 5.75 chains).

Description of monument and accessories I established to perpetuate the original location of this corner:

I set in place of the corner stone a 2 1/2" diameter by 30" aluminum pipe, with 3 1/4" diameter aluminum cap, 12 inches in the ground and raised a mound of stone 2 feet in diameter by 1 1/2 feet high (placed stone on north side of monument), from which,

6" Douglas fir bears N. 76 1/2° E., 85.4 feet, scribed "T3N R38E S10" "BT" on double blaze with a 3/4" diameter brass washer stamped "RLS 2308" nailed next to the "BT" scribbling on the lower blaze.  
Reference Monument, 5/8" by 24" rebar with 1 1/2" diameter aluminum cap, set 17" in the ground, bears S. 37°23' E., 69.1 feet, stamped "USDA-FS RM S15 69.1 FT 2308" with arrow pointing toward the corner.  
Reference Monument, 5/8" by 24" rebar with 1 1/2" diameter aluminum cap, set 13" in the ground, bears S. 26°15' W., 66.6 feet, stamped "USDA-FS RM S15 66.6 FT 2308" with arrow pointing toward the corner.  
AP-458, a 3 1/4" diameter aluminum cap set flush with the ground, bears N. 9°58' W., 57.63 feet, stamped "NFU WILDERNESS AP-458 ELEV 5000 RLS 2308 1994".

DATUM: NAD83(1991)  
STATE PLANE COORDINATES: OREGON NORTH ZONE (meters)  
Latitude: 45°44'47.05978" North  
Longitude: 118°03'21.92059" West

Northing: 233984.829 meters Easting: 2690137.023 meters

Date: July 28, 1994

Witnessed by: Rachelle Fletcher

Magnetic declination: 20° East

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*David A. Schlaich*

OREGON  
JULY 16, 1987  
DAVID A. SCHLAICH  
2308

*Revised 12-31-94*

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<i>12/14/94</i>
Date Filed	<i>12/31/94</i>
By	<i>Greg T. Balm</i>
File No.	<i>21-1994R</i>