


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File Number F-15

History of original corner establishment:

Not set.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:


At surveyed point, set 2 1/2" X 30" aluminum pipe and cap, marked:

Set pipe 20" in the ground to bedrock and mound of stone around to cap.

From which:

A 7" Pine bears S76°E, 35.2 ft. scribed CN 1/16 S10 BT.

An 8" Pine bears N69°W, 39.5 ft. scribed CN 1/16 S10 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-9s and brass washers stamped PLS 1051 on the bearing trees. Placed 54-9 on a steel fence post 5' east of the corner.



I hereby certify that the above corner monuments was established as herein described.

Witnesses: Michael E. Marks
Robert W. Wilson

October 25, 1984.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County Surveyor..... County of.....Union.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the..... day of.....November....., 19.....⁸⁴

..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 11-19-84

Date Filed 12-4-84

By G. LANGLITZ, DEPUTY

File No. 1044-84R