


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File Number F-19

History of original corner establishment:

Not set.



Description of corner evidence found:

None.

UNION COUNTY SURVEYOR	
Date Received	<u>11-19-84</u>
Date Filed	<u>12-4-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>1040-84 R</u>

Description of monument and accessories established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" X 30" aluminum pipe and cap marked:
Set pipe 24" in the ground.
From which:

A 10" Tamarack bears N58°E, 33.4 ft. scribed CN 1/16 S11 BT. A 14" Pine bears S56°E, 18.7 ft. scribed CN 1/16 S11 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-9s and brass washers stamped PLS 1051 on the bearing trees. Placed 54-9 on a steel fence post 5' east of the corner.

T3N R39E
C
N1/16 + S11
C
OR PLS 1051
1984

I hereby certify that the above corner monument was established as herein described.

Witnesses: Michael E. Marks
Robert W. Wilson

October 30, 1984.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County Surveyor..... County of.....Union.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the..... day of.....November....., 1984.

..... by

(COUNTY OFFICIAL)

(DEPUTY)