


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

G-9

History of original corner establishment:

Corner monumented by F.W. Campbell in 1884 under Contract No. 498, set a basalt stone 15" X 10" X 10", 10" in the ground, marked ¼ on West face.  
A Fir, 10" diam., N. 66° W., 57 links, mkd. ¼SBT  
A Fir, 12" diam., S. 46° E., 24 links, mkd. ¼SBT



Description of corner evidence found:

32" D.B.H. Douglas Fir, N. 66° W., 57 links, with scribes on an open face.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2½" diam. brass cap in a 2" X 30" iron pipe at record bearing and distance from remaining B.T..

Cap stamped

T3N R39E  
¼  
S 8 | S 9  
RPLS 1910  
1982

12" D.B.H. Douglas Fir, N. 10° E., 17.0', scribed ¼S9BT.

Set a brass washer marked RPLS 1910 between B and T.

Both B.Ts. have B.T. tags, attention signs and red painted bands.

Set steel fence posts 4.0'± North and South of Corner with attention, monument and boundary signs attached.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Clayton J. Martin*

OREGON  
JULY 18, 1939  
CLAYTON-JESSE MARTIN  
1910

C.J. MARTIN SURVEYING  
2751 JUNIPER ST.  
SWEET HOME, OR 97130

Office of SURVEYOR County of UNION

State of OREGON, I hereby certify that the within instrument was filed in the

for record on the 29 day of OCTOBER, 1982  
Howard L. Perry by Clayton J. Martin  
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received \_\_\_\_\_

Date Filed \_\_\_\_\_ § GPO-788-276

By \_\_\_\_\_

File No. 144-83R