
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. N-11

History of original corner establishment:

Corner was originally established by F.W. Campbell under GLO contract No. 498 in May 1884. Surveyor General's notes state "Set basalt stone, 15 X 10 X 8 ins, 12 ins. in the ground, for 1/4 sec. cor. marked 1/4 on N. face; from which: A Pine, 24 ins. diam. bears S67°W, 33 lks, dist. marked 1/4S BT. A Pine 20 ins diam. bears N28°E, 168 lks dist marked 1/4S BT.



T3N R39E

S16

Description of corner evidence found:

Found 12 X 10 X 9 ins. stone firmly set with + on tap and sim 1/4 on N. Face form which: A 30" Pine snag bears S67°W, 23.5 ft. with partially open blaze and dim scribing. A 24" Pine stump bears N 28°E, 110.0 ft. with part of foot blaze and no scribing.

Description of monument and accessories I established to perpetuate the original location of this corner:

AT center of above stone set 2 1/2" X 30 " galvanized pipe and brass cap marked: Set pipe 24" in the ground and mound S21 of stone around to cap. Placed marked stone at base of pipe. OR PLS 1051 From which by magnetic declination of N20°E: A 14" Fir bears 1980 S54°E, 24.1 ft. scribed 1/4S21 BT. A 22" Pine bears N41°W, 48.3 ft. scribed 1/4S16 BT. Painted balzes red and 6" red band around. Placed 54-3s and brass washers stamped PLS 1051 on BTs. Placed 54-4 on steel fence post 5' East of the corner.

REGISTERED PROFESSIONAL LAND SURVEYOR

> OREGON OCT. 17, 1975 BARRY B. BARBOUR

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel T. Rowland Robert Boling

June 18, 1980

			UNION COUNTY SURVEYOR	_
Office of	inty Surveyor	Union	Date Received	. \
State of Oregon	, I hereby certify that the wi	thin instrument was filed in	this effication	·
(COUNTY OF	by	(DEPUTY)	He Na. 159-83R	
Form R6-7100-57 (9/71)	•		☆ GPO798-276	