


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. P-13

History of original corner establishment:

Corner established by F.W. Campbell under GLO contract No. 498 in May, 1884. Surveyor General's notes state: "Set basalt stone, 28 X 8 X 8 ins., 22 ins. in the ground, for 1/4 sec. cor. mkd. 1/4 on W. face; from which: A pine, 20 ins. diam. bears S84°W, 57 lks. dist marked 1/4S BT. A Pine, 20 ins. diam. bears S80°E, 18 lks. dist. mkd. 1/4S BT."




Description of corner evidence found:

Found no trace of record stone. At center of mound of stone a 24" Pine bears S83°E, 12.5 ft. with open blaze and dim scribing. A 20" down pine, stump hole bears S76°W, 39.1 ft. with BT. visible.

Description of monument and accessories established to perpetuate the original location of this corner:

At center of above point set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 18" in the ground and mound of stone around to cap.

From which by magnetic declination of N20°E: A 12" Pine bears N65°W, 103.5 ft. scribed 1/4S21 BT. Placed 54-3s and brass washers stamped PLS 1051 on BTs. Painted blazes red and 6" red band around. Placed 54-4 on steel fence post 5' North of the corner.



I hereby certify that the above corner was monument was reestablished as herein described.

Witnesses: Daniel T. Rowland
Robert Boling

June 18, 1980

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County Surveyor..... County of..... Union

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 3rd day of.....J.U.L.Y....., 1980

..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed _____

By _____

File No. 165-83R

☆ GPO-788,272