


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

X-9

History of original corner establishment:

Survey was performed by Rufus Moore, Deputy Surveyor, under contract No. 437, dated June 3, 1882. He set a fir post for the $\frac{1}{4}$ corner common to Sections 32 and 33 T 3 N R 39 E WM. The bearing trees were:
 A fir 10" dia. bears N 82 E, 54 lks. dist. scribed $\frac{1}{4}$ S BT.
 A fir 12" dia. bears West, 50 lks. dist. scribed $\frac{1}{4}$ S BT.



Description of corner evidence found:

Found a white fir, now 28" dia. and alive in Section 33; the face being chopped out to expose the scribing $\frac{1}{4}$ S.
 Found a stump hole fitting the bearing and distance in Section 32; no other evidence available.

Description of monument and accessories established to perpetuate the original location of this corner:

I set a stamped 2 $\frac{1}{2}$ " brass cap on a 30" galv. iron pipe at the $\frac{1}{4}$ corner location, by using the GLO call bearing and distance from the live bearing tree. I then placed a mound of stone around the monument. I then set new bearing trees as follows:
 A larch 10" dia. bears N 52 E, 58.0 feet (slope distance) and scribed $\frac{1}{4}$ S S 33 BT.
 A white fir 11" dia. bears N 67 W, 40.0 feet (slope distance) and scribed $\frac{1}{4}$ S S 32 BT.

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

James H. Hambleton
 3-20-78

OREGON
 JULY 10, 1964
 JAMES H. HAMBLETON
 645

**UNION COUNTY
 SURVEYOR**

Date Received _____

Date Filed _____

By _____

File No. 175-83R
REG-700-270

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)