


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-3

History of original corner establishment:

Corner established in November, 1884 by H.D. Gradon under G.L.O. Contract #517. Surveyor's General's notes state: "Set a basalt stone 10 x 10 x 8 ins. 7 ins. in the ground for 1/4 Sec. corner marked 1/4 on N face, from which: A Pine 30 ins. diam. bears N70°W, 16lks. dist. marked 1/4 S.B.T.. A Pine 30 ins. diam. bears S80°E, 22lks. dist. marked 1/4 S.B.T.."



Description of corner evidence found:

Found loose 10" x 10" x 8" stone and wood stick.

No marks found on stone.

Two large Pines appear to be record BTs and at a point are: A Pine 33" in dia. bears S80°E, 14.9 feet, face scribed 1/4S. A Pine 33" in dia. bears N60°W, 10.9 feet, face with grown over blaze.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2" x 30" galvanized pipe with brass cap marked: Set pipe 24" in the ground, and placed stone at base of pipe.

T3N R40E
S6
1/4 S7
OR PLS 1051
1978

From which: A Pine 28" in dia. bears N14°W, 56.3 feet, scribed 1/4S6BT. Painted blazes red and 6" red band around. Placed 54-3s and 54-4s on new BT. Placed brass washer stamped PLS 1051 on foot blazes. Placed 54-4s on old BTs and marked existing 54-3s. Placed 54-2 and 54-4 on steel fence post 5' West of corner. Location tag on NW BT.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Dan T. Rowland

October 13, 1978

REGISTERED PROFESSIONAL LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of... County Surveyor... County of Union
State of Oregon... I hereby certify that the within instrument was filed in this office
for record on the 20 day of November 1978
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Date Received
Date Filed
By
File No. 189-83R