

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-9

History of original corner establishment:

Survey was performed by Herman D. Gradon, Deputy Surveyor under Contract No. 517, dated Sept. 30, 1884. He set a stone 14 x 10x 6 for the Section Corner common to Sec's 4, 5 & 8, 9, T 3 N, R 40 E, WM. The bearing trees were:
A tamarack 24" dia. bears N 13 E, 42 lks. dist. marked T 3 N, R 40 E S 4 BT.

A fir 24" dia. bears S 42 E, 17 lks. dist. marked T 3 N R 40 E S 9 BT.

A fir 20" dia. bears S 31 W, 56 lks, dist. marked T 3 N R 40 E S 8 BT.

A fir 24" dia. bears N 64 W, 54 lks. dist. marked T 3 N R 40 E S 5 BT.

Description of corner evidence found:

Found a stone 14 x 10 x 6 with 5 notches on the south face and 4 notches on the east face, also I found--
A standing dead tamarack in section 4, scribed T 3 N R 40 E S 4 BT.
A rotted stump and log with a ledgible scribe T 3 N R 40 E S 9 BT.
Only stump holes remain of the other two bearing trees.

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a stamped 2 1/2" brass cap on a 30" galv. iron pipe at the Section Corner location, I turned the stone upside down and buried it in the hole along side the brass cap.
I then set new bearing trees as follows:
A white fir 10" dia. bears N 72 E, 19.6 feet and scribed T 3 N R 40 E S 4 BT.

A larch 13" dia. bears S 80 E, 36.3 feet and scribed T 3 N R 40 E S 9 BT.
A red fir 11" dia. bears S 23 W, 16.6 feet and scribed T 3 N R 40 E S 8 BT.
A red fir 17" dia. bears N 78 W, 39.9 feet and scribed T 3 N R 40 E S 5 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
1-17-78

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Office of Rural Dept County of Union
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 7 day of January 1978
SHIRLEY L. BOLIN by George W. G. G. G.
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR
Date Received _____
Date Filed _____
By _____
File No. 192-83R

+

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-9

History of original corner establishment:

Corner was originally established by Deputy Herman D. Gradon in 1884 under contract #517.

Set: Stone 14x10x6, 5 notches on S and 4 on E. face.


Marked: 24" Tamarack N13E, 42 lks.- 24" Fir S42E, 17 lks.- 20" Fir S31W, 56 lks.-24" Fir N64W, 54 lks..

Corner was reestablished by ORLS 645 in 1977.

Found: Stone 14x10x6 with 5 notches on South face and 4 notches on East face. Standing dead Tamarack in section 4- Rotted stump and log. Both with scribing visible.

Set: Stamped 2½" brass cap on a 30" gal. iron pipe. Buried stone along side.

Marked: 10" Wh. Fir N72E, 19.6' - 13" Larch S80E, 36.3'- 11" Red Fir S23W, 16.6'- 17" Red Fir N78W, 39.9'.



Description of corner evidence found:

2" gal. iron pipe with a 2½" brass cap firmly set 3" above ground. Original stone along side. Stamped:

T3N

S5 | S4
S8 | S9

Orig. 24" now 30" down Tamarack snag-stood N15E, 28.5' to center. Full scribing visible. (record N13E, 27.7').

R40E

1977

Orig. 24" now Northerly slab of 24" D-Fir S48E, 13.2' (record S42E, 11.2') Full scribing visible on double blaze. Of note, the lower blaze is just above the ground line.

ORLS 645

1977 10" now 11" Wh. Fir N68E, 19.6' (record N72E) Scribing visible on nearly healed blaze.

1977 13" now 15" Tamarack S82E, 37.0' (record S80E, 36.3') Healed double blaze.

1977 11" now 10" D-Fir S25W, 17.3' (record S23W, 16.6') Healed double blaze.

1977 17" now 20" D-Fir N80W, 40.9' Healed double blaze.

Description of monument and accessories established to perpetuate the original location of this corner:


Nailed 54-9 and 54-3 signs to orig. BT's and painted bands and blazes red on all BT's.

Set guard post North with 54-2 and 54-9 signs.

Dec. 20.

Witnesses: Norman Larson and Carole Bishop.

Work was done in June 1994.



Larry D. Bishop



EXPIRES 12/31/95

UNION COUNTY SURVEYOR

Date Received 9/27/94

Date Filed 10/22/94

By *Gregory T. Bark*

File No. 081-1994R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)