
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-15

History of original corner establishment:

Corner established by H. D. Graden under GLO contract No. 517, in November, 1884. Surveyor General's notes state: "Set a basalt stone 16 x 12 x 7 ins., 11 ins. in the ground, for 1/4 sec. cor., marked 1/4 on N.face; From which: A pine, 18 ins. in diam., bears N12°W, 49 lks. dist., marked 1/4 S BT. A pine, 8 ins. in diam., bears S18°W., 139 lks. dist., marked 1/4 S BT."



Description of corner evidence found:

Found 15 x 9 x 5 inch stone in mound of stone, clearly marked 1/4 on north face. From which a 32" pine bears N13°W, 33.6 ft., with letter S visible. A 12" pine bears S16°W, 92.5 ft. (slope), 80.9 ft.(horz). Magnetic variation used: N20°E.

Description of monument and accessories I established to perpetuate the original location of this corner:

T3NR40E At center of above described stone, set 2 1/2" x 30" , S3 galvanized pipe with brass cap marked: Set pipe 16" in the ground to bedrock and mound of stone around to cap. Placed marked stone at OR PLS 1051 base of pipe. From which: A 9" pine bears N35°E, 40.0 ft., scribed 1/4 S3 BT. Placed 54-3 and brass washer 1979 stamped PLS 1051 on new BT. Placed 54-3s on old BTs. Painted blazes red and 6" red band around. Placed 54-4 on steel fence post 5' East

PROFESSIONAL LAND SURVEYOR 13 ortour OREGON OCT. 17, 1975 BARRY B. BARBOUR 1 0 5 1

REGISTERED

of corner.

I hereby certify that the above corner monument was reestablished as herin described.

David L. Landers Daniel T. Rowland Witnesses:

S10

Ray McVey

May 30, 1979

Office ofCounty.Surveyor	the within instrument was filed in	this office Care Constitution of the Care Care Care Care Care Care Care Car
(COUNTY OFFICIAL)	(DEPUTY)	Date kacored
Form R6-7100-57 (9/71)		₩ GPO 799-509
		195-83R