


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. J-15

History of original corner establishment:

Corner established by H. D. Graden under GLO contract No. 517, in November, 1884. Surveyors General's notes state: "Set a basalt stone 16 x 13 x 8 ins. in the ground, for 1/4 sec. cor., marked 1/4 on N. face from which: A pine 12 ins. in diam., bears S41°W, 163 lks. dist. A pine 20 ins. in diam. bears N39°E, 148 lks. dist."




Description of corner evidence found:

Found 15 x 12 x 8 inch basalt stone clearly marked 1/4 on north face in a mound of stone from which a 28" pine bears N40°E, 98.6 ft. with partially grown over blazes.

Magnetic Variation used: N20°E.

Description of monument and accessories established to perpetuate the original location of this corner:

At center of above described stone, set 2 1/2" by 30" galvanized pipe with brass cap marked: Set pipe 8" in the ground to bedrock and mound of stone around to cap. Placed marked stone at base of pipe. From which: A 16" pine bears S42°E, 145.8 ft., scribed 1/4 S15 BT. Placed 54-3 and brass washer stamped PLS 1051 on new BT. Painted blazes red and 6" band around. Old BT has 54-3. Placed 54-4 on steel fence post 4' East of corner.



I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers
Daniel T. Rowland
Ray McVey

May 29, 1979

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

OREGON
OCT. 17, 1979
BARRY B. BARBOUR
1051

Office of _____ County Surveyor _____ County of _____ Union _____
State of _____ Oregon _____, I hereby certify that the within instrument was filed in this office
for record on the 19th day of _____ June _____, 1979.

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed _____

By _____

File No. 207-03R