


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

Index File No. J-17

**History of original corner establishment:**

Corner established by H. D. Graden under GLO contract No. 517, in November, 1884. Surveyors General's notes states: "Set a basalt stone 16 x 12 x 9 ins., 11 ins. in the ground for cor. to secs. 10, 11, 14, and 15, marked with 4 notches on the S. and 2 notches on the E. edge. From which: A pine 10 ins. in diam. bears N40°E, 11 lks. dist. marked T3NR40E S11 BT. A pine 24 ins. in diam. bears S30°E, 12 lks. dist. marked T3NR40E S14 BT. A fir 8 ins. in diam. bears S20°W, 19 lks. dist. marked T3NR40E S15 BT. A fir 6 ins. in diam. bears N50°W, 23 lks. dist. marked T3NR40E S10 BT."



**Description of corner evidence found:**

No trace of corner stone or mound found. Corner falls on very steep ground. Southeast BT dead and down with faint scribing. No trace of S.W. BT and N.W. BT. A 24" fir (not pine) partially opened blaze and letter S visible. From which, measures S40°W, 7.2 ft. and stump hole of down S.E. BT measures S30°E approximately 8 ft.

Magnetic variation used: N20°E.

**Description of monument and accessories established to perpetuate the original location of this corner:**

At the above described point set 2 1/2" x 30" galvanized pipe with brass cap marked: Set pipe 18" in the ground and mound of stone around to cap.


From which: A 12" pine bears N80°E, 64.0 ft. scribed T3NR40E S11 BT. A 15" pine bears S70°E, 33.5 ft. scribed T3NR40E S14 BT. An 18" fir bears S27°W, 133.9 ft. scribed S15 BT. A 20" fir bears N43°W, 56.0 ft. scribed T3NR40E S10 BT. Placed 54-3s and brass washer stamped PLS 1051 on BTs. Painted blazes red and 6" red band around. Placed 54-3s on old BTs. Placed 54-4 on steel fence post 5' South of corner.

T3NR40E  
S10 | S11  
S15 | S14  
OR PLS 1051  
1979

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: David L. Landers  
Daniel T. Rowland  
Ray McVey

May 29, 1979



*Barry B. Barbour*  
OREGON  
OCT. 17, 1975  
BARRY B. BARBOUR  
1051

Office of... County Surveyor... County of... Union...  
Oregon  
State of... I hereby certify that the within instrument was filed in this office  
for record on the 19<sup>th</sup> day of... June... 1979

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

