CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History	of original	corner	establishment:
TI.			su sumbut:

The exterior lines of township 3 South Range 33½ East were orginally established by Rufus L. Moore under Contract No. 451, dated June 12, 1882. The original notes state that at the corner a 4 ft. long by 4 inch square post was set 24 inches in the ground

A 10" pine bears N 35°E 33 LK (21.8 ft) marked T 25, R 33½E S35BT A 24" tamerack bears S 40°W 6 LK (4.0 ft.) marked T35 R 33½E S3BT A 36" pine bears S 73°E 12 LK (7.9 ft.) marked T3S R 33½E S2BT A 8" fir bears N31°W 22 LK (14.5 ft.) marked T25 R 33½E S34BT

A	- 17
DIAGRAM TAS S34	R33e 535
83	
T3S	R331/4E

No record of subsequent re-monumentation found in County records. Description of corner evidence found:

Found no evidence of original monument, set from 3 original Bt's by the average distance intersection. A $22\frac{1}{2}$ " tamarack bears 548° W 5.0' to center of tree, open blaze scribing visible, dying.

A 40" red fir bears S 75°E 9.5 ft to center of tree with blaze healed, dead.

A 8" douglas fir bears N 31°W 14.0 ft to center of tree with healed blaze, dead.

Description of monument and accessories I established to perpetuate the original location of this corner.

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 24 inches in ground and surrounded with a mound of stones.

Set a steel fence post on Township line W of corner and attached signs 54-2 and 54-4. Established 4 new BT's: A 14" tamarack bears S60°E 23.9 ft, scribed T3S R33½E S2 BT

A 18" fir bears \$14°W 34.5 ft, scribed T3\$ R33½E \$3 BT.

A 9-3/4" fir bears N5710 E 26.5 ft, scribed T2S R33E S35 BT.

A 12½" fir bears N23°W 15.1 ft, scribed T2S R33E S34 BT.

New BTS have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush. Attached sign 54-3 and 54-4 and painted red ring around all BT's.

Used steel	tape and magnetic compass w	ith 1930 east various		
See Map of Survey		th 19½° east variation. Measured to center of BT's.		
This Corner	Set June 29, 1979	PROFESSIONAL LAND SURVEYOR	TAS R33E	
Witnesses:	Greg Flowers, L.S.I.T. Brent Reynolds	William R. Wells	S34 S35 S3 Sa	

Brent Reynolds OREGON JULY 22, 1977 WILLIAM R. WELLS

360-84R

State of County Surveyor	s filed in this office
(COUNTY OFFICIAL) by	SURVEYOR
Form R6-7100-57 (9/71)	Date Received_
	Date Filed
	By