CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The exterior lines of Township 3 South, Range 33½ East were originally established by Rufus L. Moore under Contract No. 451 dated June 12, 1882
The original notes state that at the corner a 13"x12"x6" basalt stone was set 9 inches in the ground from which: A 10" tamarack bears N 50°E 60LK (39.6 ft) marked 1/4 S BT

A 8" tamarack bears S 31°W 100 LK (66.0 ft) marked 1/4 S BT

DIAGRAM Tas R33E T3S R331/aE

No record of subsequent re-monumentation found in County records. Description of corner evidence found:

No evidence of original monument or bearing trees found, corner re-established by survey

Description of monument and accessories I established to perpetuate the original location of this corner:

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 24 inches in ground and surrounded with a mound of stones.

Set steel fence post on Township line West of corner and attached signs 54-2 and 54-4. Established 2 new BT's: A 8" fir bears N. 25°W 12.7 ft, scribed \$\$35 BT.

A 15" fir bears S3°W 16.8 ft, scribed $\frac{1}{4}$ S2 BT.

New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush. Attached sign 54-3 and 54-4 and painted red ring around all BT's.

Location poster located 500'+ West of corner near gate where jeep road goes through fence.

See Man of	rape and magnetic compass wi	th 19½° east variation. Measured to center of BT's.		
See Map of Survey This Corner Set June 30, 1979		REGISTERED PROFESSIONAL LAND SURVEYOR	Tas R33E 335	
Witnesses:	Greg Flowers, L.S.I.T. Brent Reynolds	Willia R. Wells OREGON JULY 22, 1977 WILLIAM R. WELLS	T3S R331/2E 1979 PLS 1106	

Office of County Surveyor County of State of Oregon	Union	
for record on the day of	strument was filed in this office	
(COUNTY OFFICIAL)	(DEPUTY)	SURVEYOR
R6-7100-57 (9/71)		Date Received

Date Filed

Form F