

T3S33 1/2 A23

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33 1/2 E., Willamette Meridian, Oregon

CHAINS

~~A fir, 19 ins. diam., bears N. 75° W., 31 1/2 lks.
dist., mkd. T2S R33E S36 BT.~~

~~Deposit corner stone alongside iron post.~~

~~North Boundary, T. 3 S., R. 33 1/2 E.,
Willamette Meridian, Oregon~~

(Remonumenting a corner established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the
Tp., monumented with the original unmarked basalt stone,
16 x 16 x 3 ins., loosely set in a mound of stone, 2 ft.
base, 1 ft. high, from which the only remaining original
bearing tree:

A pine, 25 ins. diam., bears S. 41° E., 202 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 2 S R 33 E
1/4 S 36
S 1
T 3 S R 33 1/2 E
1977

from which a new bearing tree

A pine, 12 ins. diam., bears N. 50° E., 43 lks.
dist., mkd. 1/4 S36 BT.

Deposit corner stone alongside iron post.

(Remonumenting a corner established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882,
and redescribed by John C. Arnold,
U. S. Deputy Surveyor, in 1891)

~~The cor. of secs. 1, 2, 35, and 36, monumented with the
original basalt stone, 16 x 10 x 10 ins., firmly set 10
ins. in the ground, mkd. with 1 notch on E. and 2 notches
on W. edges, from which the remains of the original
bearing trees:~~

~~A pine snag, 11 ins. diam., bears S. 56° W., 36
lks. dist., with scribe marks T3S R33 1/2 E S2 BT
visible on open blaze. (Record, S. 50° W.)~~

~~A pine snag, 24 ins. diam., bears N. 48° W., 37
lks. dist., with scribe marks R33 1/2 E S35 visible
on open and burned blaze.~~

~~At the corner point~~

~~Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.~~

T3S33 1/2 A23

T3S33 1/2 A21

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By J. G. L. DEPUTY

File No. 363-2013R