

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33 $\frac{1}{2}$ E., Willamette Meridian, Oregon

CHAINS

T 2 S R 33 E
S 35 | S 36
S 2 | S 1
T 3 S R 33 $\frac{1}{2}$ E
1977

from which new bearing trees

A grand fir, 9 ins. diam., bears N. 42° E., 20
lks. dist., mkd. T2S R33E S36 BT.

A grand fir, 12 ins. diam., bears S. 70° E., 12
lks. dist., mkd. T3S R33 $\frac{1}{2}$ E S1 BT.

A grand fir, 12 ins. diam., bears S. 43° W., 17 $\frac{1}{2}$
lks. dist., mkd. T3S R33 $\frac{1}{2}$ E S2 BT.

A grand fir, 15 ins. diam., bears N. 56 $\frac{1}{2}$ ° W., 31
lks. dist., mkd. T2S R33E S35 BT.

Deposit corner stone alongside iron post.

Subdivisions, T. 3 S., R. 33 $\frac{1}{2}$ E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 1, 2, 11, and 12, determined at record
bearing and distance from the remains of the original
bearing trees:

A fir, 18 ins. diam., bears S. 10° W., 7 lks.
dist., with fragmentary scribe marks visible
on partially healed blaze.

A fir, 16 ins. diam., bears N. 37° W., 17 lks.
dist., with scribe marks 3S R33E S visible
on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 3 S R 33 $\frac{1}{2}$ E
S 2 | S 1
S 11 | S 12
1977

from which new bearing trees

A fir, 7 ins. diam., bears N. 34 $\frac{1}{2}$ ° E., 28 lks.
dist., mkd. T3S R33 $\frac{1}{2}$ E S1 BT.

A fir, 10 ins. diam., bears S. 58° E., 68 lks.
dist., mkd. T3S R33 $\frac{1}{2}$ E S12 BT.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, determined at record
bearing and distance from the remains of the original
bearing trees:

A pine snag, 40 ins. diam., bears N. 63° E., 102
lks. dist., with scribe marks $\frac{1}{4}$ S visible on
open blaze.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 364-2013R

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33½ E., Willamette Meridian, Oregon

CHAIN

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 3 S R 33½ E
¼
S 2 | S 1
1977

from which new bearing trees

A pine, 15 ins. diam., bears N. 60° E., 40 lks. dist., mkd. ¼ S1 BT.

A pine, 18 ins. diam., bears N. 59° W., 114 lks. dist., mkd. ¼ S2 BT.

The cor. of secs. 2, 3, 10, and 11, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 70° E., 20 lks. dist., with a down pine alongside, 12 ins. diam., with scribe marks BT visible on open blaze. (Record, larch)

A root hole, bears S. 30° E., 7 lks. dist., with a down pine alongside, 13 ins. diam., with scribe marks S11 visible on open blaze. (Record, larch)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 33½ E
S 3 | S 2
S 10 | S 11
1977

from which new bearing trees

A grand fir, 8 ins. diam., bears N. 60° E., 43 lks. dist., mkd. T3S R33½E S2 BT.

A grand fir, 11 ins. diam., bears S. 60° E., 25 lks. dist., mkd. T3S R33½E S11 BT.

A grand fir, 6 ins. diam., bears S. 65° W., 4 lks. dist., mkd. T3S R33½E S10 BT.

A grand fir, 7 ins. diam., bears N. 56° W., 17 lks. dist., mkd. T3S R33½E S3 BT.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 364-2013R