

T3S33 $\frac{1}{2}$ E21

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33 $\frac{1}{2}$ E., Willamette Meridian, Oregon

CHAINS

T 2 S R 33 E
S 35 S 36
S 2 S 1
T 3 S R 33 $\frac{1}{2}$ E
1977

from which new bearing trees

A grand fir, 9 ins. diam., bears N. 42° E., 20 lks. dist., mkd. T2S R33E S36 BT.

A grand fir, 12 ins. diam., bears S. 70° E., 12 lks. dist., mkd. T3S R33 $\frac{1}{2}$ E S1 BT.

A grand fir, 12 ins. diam., bears S. 43° W., 17 $\frac{1}{2}$ lks. dist., mkd. T3S R33 $\frac{1}{2}$ E S2 BT.

A grand fir, 15 ins. diam., bears N. 56 $\frac{1}{2}$ ° W., 31 lks. dist., mkd. T2S R33E S35 BT.

Deposit corner stone alongside iron post.

Subdivisions, T. 3 S., R. 33 $\frac{1}{2}$ E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from the remains of the original bearing trees:

A fir, 18 ins. diam., bears S. 10° W., 7 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 16 ins. diam., bears N. 37° W., 17 lks. dist., with scribe marks 3S R33E S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 33 $\frac{1}{2}$ E
S 2 S 1
S 11 S 12
1977

T3S33 $\frac{1}{2}$ E21

**UNION COUNTY
SURVEYOR**

Date Received 3/15/13

Date Filed 3/15/13

By J. H. DEPUTY

File No. 366-2013R

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, determined at record bearing and distance from the remains of the original bearing trees:

A pine snag, 40 ins. diam., bears N. 63° E., 102 lks. dist., with scribe marks $\frac{1}{4}$ S visible on open blaze.

T3S33 $\frac{1}{2}$ C21