


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 20x15x10, from which a 4" Fir bears S30°W, 27 lks.; a 4" Pine bears S36°E, 16 lks.; an 8" Tamarack bears N16°E, 25 lks.; and a 4" Pine bears N69°W, 30 lks.

Index File No. R-17



Description of corner evidence found:

Found BLM 3 1/4" brass cap on 2 1/2" iron pipe, rising 5", stamped:

Bearing trees found:

- A 12" D. Fir bears N34 1/4°W, 31.7 ft., scribing visible "T3S R33 1/2E S22 BT".
- A 7" D. Fir bears N 7 1/4°E, 10.9 ft., scribing visible "T3S R33 1/2E S23 BT".
- An 11" L. Pine bears S36°E, 11.0 ft., scribing visible. Cut to verify.
- A 17" D. Fir bears S30°W, 18.3 ft., blaze healed.

T3S R33 1/2E

S22	S23
S27	S26

1975

Description of monument and accessories | established to perpetuate the original location of this corner:

New BT:

A 6" D. Fir bears S42°E, 14.4 ft., scribed T3S R33 1/2E S26 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From the intersection of 2115 & 2115-127, go easterly on 2115 1/4 mi. Walk straight south 450 ft. to corner.

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>B. A. Sutton</i>
OREGON JULY 13, 1979 B. A. SUTTON 1848

I hereby certify the above described corner monument and/or accessories was established as described on June 7, 1984.

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

<b>UNION COUNTY SURVEYOR</b>
Date Received <u>7-2-84</u>
Date Filed <u>7-3-84</u> <small>☆ GPO-798-276</small>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>891-84 R</u>

Remonumentation of Certain Original Corner Points,  
T. 3 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

A juniper, 18 ins. diam., bears S. 69° E., 142 lks. dist., with scribe marks T3S R33½E S35 BT visible on partially healed blaze. (Record, S. 70° E., 144 lks.)

A fir, 40 ins. diam., bears S. 22° W., 30 lks. dist., with illegible scribe marks visible on partially healed blaze.

A pine, 22 ins. diam., bears N. 42° W., 47 lks. dist., with scribe marks T3S R33½E S27 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 3 S R 33½ E	
S 27	S 26
S 34	S 35
1975	

from which a new bearing tree

A fir, 14 ins. diam., bears N. 57° E., 14½ lks. dist., mkd. T3S R33½E S26 BT.

Deposit corner stone alongside iron post.

The ½ sec. cor. of secs. 26 and 27, determined at record bearing and distance from which the remains of the original bearing trees:

A fir, 14 ins. diam., bears S. 8° E., 62 lks. dist., with scribe marks / 4 S visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, to solid rock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T 3 S R 33½ E	
½	
S 27	S 26
1975	

from which a new bearing tree

A pine, 20 ins. diam., bears N. 2½° W., 69 lks. dist., mkd. ½ S27 BT.

The cor. of secs. 22, 23, 26, and 27, determined at record distance from the remains of the original bearing trees:

A pine, 10 ins. diam., bears S. 36° E., 16 lks. dist., with scribe mark S visible on partially healed blaze.

A fir, 12 ins. diam., bears S. 31½° W., 27 lks. dist., with healed blaze. (Record, S. 30° W.)

UNION COUNTY  
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 369-20132

Remonumentation of Certain Original Corner Points,  
T. 3 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 33½ E  
S 22 | S 23  
S 27 | S 26  
1975

from which new bearing trees

A fir, 6 ins. diam., bears N. 7½° E., 17 lks. dist., mkd. T3S R33½E S23 BT.

A fir, 9 ins. diam., bears N. 34½° W., 48 lks. dist., mkd. T3S R33½E S22 BT.

The ½ sec. cor. of secs. 14 and 23, monumented with a basalt stone, 16 x 13 x 8 ins., firmly set 4 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A root hole, bears S. 68° E., 117 lks. dist., with a down and decayed pine alongside, 10 ins. diam., with scribe marks BT visible on decayed blaze.

A pine snag, 15 ins. diam., bears N. 84° W., 80 lks. dist., with scribe marks ¼ S visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 33½ E  
S 14  
S 23  
1975

from which new bearing trees

A pine, 10 ins. diam., bears S. 61½° E., 79 lks. dist., mkd. ¼ S23 BT.

A pine, 7 ins. diam., bears N. 75½° W., 32 lks. dist., mkd. ¼ S14 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 10, 11, 14, and 15, monumented with a basalt stone, 13 x 10 x 8 ins., firmly set 7 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A decayed fir stump, 14 ins. diam., bears N. 36° E., 72 lks. dist., with scribe marks T3S R33½E S11 visible on decayed blaze.

A fir, 22 ins. diam., bears S. 68° E., 34 lks. dist., with healed blaze. (Record, 41 lks.)

A root hole, bears S. 42° W., 34 lks. dist., with a down and decayed fir alongside, 36 ins. diam., no marks visible.

UNION COUNTY  
SURVEYOR

Date Received

3/15/13

Date Filed

3/15/13

By

File No.

369-2013E