


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-24

History of original corner establishment:

Corner was established by Survey No. 028-2004.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

I establish the corner point by survey and set a 5/8" x 30" rebar with 1 1/4" yellow plastic cap marked "OR PLS 1106, WA PLS 17372". Set a steel fence post 0.5' North of corner monument.

From the new corner monument:

- A 12" Douglas fir bears N 60° E, 18.5 feet scribed E 1/16 S25 BT.
- A 15" Ponderosa pine bears S 67° E, 14.0 feet. (Reference only, not scribed).
- A 7" Douglas fir bears S 53° W 46.3 feet scribed E 1/16 S36 BT.

Scribed bearing trees have a 3/4" brass washer stamped "PLS 1106" nailed to face of blaze.

This corner was monumented on September 13, 2004.

Used magnetic compass with 18° East declination and a steel tape to measure bearing tree accessories.

Witness: Jason Wells, LSIT

Office of.....County of.....
State of, I hereby certify that the within instrument was filed in this office for record on theday of, 20.....

UNION COUNTY
SURVEYOR

Date Received 10/1/04

Date Filed 10/10/04

By [Signature]

File No. 043-20042

(DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

renews 6-30-04