


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-21

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a post, from which a 4" Pine bears N75°W, 6 lks. and a 4" Pine bears S56°E, 8 lks.



Description of corner evidence found:

Found mound of stones with 14x10x6 stone with faint "1/4"

See narrative on plat of survey of S36, T3S, R33 1/2E, by Sutton Surveying for explanation of this corner.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2" x30" aluminum capped aluminum pipe rising 18" in a mound of stones. Cap stamped:

T3S	R33	1/2E
1/4		
S35		S36
1984		
RLS 1848		

New BT's:

- A 13" P. Pine bears N41°E, 410.9 ft., scribed 1/4 S36 BT.
- A 9.5" D. Fir bears S83 3/4°W, 103.2 ft., scribed 1/4 S35 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Set metal fence post 5 ft. south of corner.

Compass Declination: 19 1/2°E

Witness: J. Sutton

From 2115, southwesterly & southerly on 2115-108 2.3 mi. to "Y". Take right fork south .2 mi. NE BT is on the right edge of the road.

I hereby certify the above described corner monument and/or accessories was established as described on May 29, 1984.



Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>7-2-84</u>
Date Filed	<u>7-23-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>903-84 R</u>