


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-21

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 18x15x8, from which an 11" Pine bears N46°W, 220 lks. and a 12" Pine bears N50°E, 189 lks.



Description of corner evidence found:

Found original stone.

Bearing Trees Found:

A 16" L. Pine, dead and down, bears N46°W, 146.0 ft., B&S visible.
Rotted remains of original BT bears N50°E, 124.8 ft.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2 1/2" x 30" aluminum capped aluminum pipe, stamped:
Set original stone in mound north of corner.

SC	
T3S R33 1/2E	
S35	S36
1984	
RLS 1848	

New BT's:

A 6.5" L. Pine bears N30 1/2°W, 14.4 ft.,
scribed T3S R33 1/2E S35 SC BT.
A 6" D. Fir bears N57 1/4°E, 84.5 ft.,
scribed T3S R33 1/2E S36 SC BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal fence post 4 ft. north of corner.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From the intersection of 2110-710. & 2110-670, northerly .6 mi. to the posted line. Follow posted line west 1,000 ft. to corner.

I hereby certify the above described corner monument and/or accessories was established as described on May 16, 1984.



Office of..... County of.....

State of..... I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	<u>7-2-84</u>
Date Filed	<u>7-3-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>905-84 R</u>