


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-24

History of original corner establishment:

Corner was established on Survey No. 028-2004.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

I establish the corner point by survey and set a 5/8" x 30" rebar with 1 1/4" yellow plastic cap marked "OR PLS 1106, WA PLS 17372". Set steel fence post 0.5 foot South of corner monument.

From the new corner monument:

A 10" lodgepole pine bears N 28° W 44.9 feet scribed E 1/16 S36 BT.  
A 7" lodgepole pine bears S 51° W 26.3 feet scribed E 1/16 S 36 BT.

New bearing trees have a 3/4" brass washer stamped "PLS 1106" nailed to face of blaze.

This corner was monumented on September 13, 2004.

Used magnetic compass with 18° East declination and a steel tape to measure bearing tree accessories.

Witness: Jason Wells, LSIT

Office of.....County of.....  
State of ....., I hereby certify that the within instrument was filed in this office for record on the .....day of ....., 20.....

.....by.....  
(COUNTY OFFICIAL) (DEPUTY)

<b>UNION COUNTY</b>
SURVEYOR
Date Received <u>10/1/04</u>
Date Filed <u>10/10/04</u>
By <u>[Signature]</u>
File No. <u>045-2004R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR
---

*William R. Wells*

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106
---

*renews 6-30-06*