


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

In 1882, under Glo Contract No. 451, Rufus S. Moore set a stone 18x12x12. A 12" Pine bears N23°W, 41 lks. and a 14" Pine bears N57°E, 118 lks.

Index File No. L-25




Description of corner evidence found:

Fd. BLM3 1/4" brass cap on 2 1/2" iron pipe in mound of stones 4 feet in diameter at base, rising 1 ft. in mound, stamped:

Bearing Trees Found:

- A 13" Juniper bears S28°W, 24.9 ft., scribed "1/4 S13 BT".
- A 22" P. Pine bears N58 1/2°W, 76.1 ft., scribed "S13 BT".
- An 18" P. Pine bears N57°E, 118 lks., blaze healed.



Description of monument and accessories established to perpetuate the original location of this corner:

Added earth and additional stones to stabilize mound. Cap now rises 8" in mound.

Set post 1 ft. north of corner in mound of stones.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982.

Compass Declination: 19 1/2°E

Witness: N. Petz

On USFS Rd. 2115-235, from 2115 southeasterly 1/2 mi. Northeast BT is on the right side of the road. Corner is about 75 ft. right, down the hill.

I hereby certify the above described corner monument and/or accessories was established as described on September 14, 1983.



Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY SURVEYOR

Date Received 7-2-84
Date Filed 7-3-84
By G. LANGUITZ, DEPUTY
File No. 869-84R

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

A pine snag, 22 ins. diam., bears S. 22° W., 68 lks. dist., with scribe marks T3S R33E S24 visible on partially healed blaze.

A root hole, bears N. 21° W., 99 lks. dist., with a down and decayed pine snag alongside, 16 ins. diam., with scribe marks BT visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S | T 3 S
S 13 | R 33½ E
S 24 | S 15
R 33 E
1975

from which new bearing trees

A fir, 5 ins. diam., bears S. 51½° W., 21 lks. dist., mkd. X BT.

A fir, 7 ins. diam., bears N. 78½° W., 15 lks. dist., mkd. T3S R33E S13 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with the original basalt stone, 18 x 12 x 12 ins., firmly set 5 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A pine, 18 ins. diam., bears N. 57° E., 118 lks. dist., with healed blaze.

A pine stump, 8 ins. diam., bears N. 25½° W., 41 lks. dist., with scribe marks BT visible on decayed blaze. (Record, N. 23° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground, to solid rock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T 3 S
R 33 E | R 33½ E
¼ S 13
1975

from which new bearing trees

A juniper, 12 ins. diam., bears S. 28° W., 40 lks. dist., mkd. ¼ S13 BT.

A pine, 22 ins. diam., bears N. 58½° W., 115 lks. dist., mkd. ¼ S13 BT.

Deposit corner stone alongside iron post.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 358-2013P

T3S33L25