


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Index File No. N-21

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 20x18x4, from which a 36" Pine bears N12°W, 40 lks.; a 24" Pine bears N57°E, 241 lks.; a 10" Pine bears S58°E, 131 lks.; and a 10" Fir bears S60°W, 35 lks.



Description of corner evidence found:

Found a 3 1/4" BLM brass cap on a 2 1/2" iron pipe rising 6" in mound, stamped:

T3S R33E

S14 | S13

S23 | S24

1977

Bearing Trees Found:

- A 28" P. Pine bears N57°E, 156.7 ft., scribing visible "T3S S13".
- A 24" P. Pine bears S58°E, 87.6 ft., dead standing, blaze healed.
- A 9" Fir bears S60°W, 23.1 ft., dead standing, scribing visible "S23 BT".
- A 24" Fir bears S73°W, 22.8 ft., scribing visible "T3S R33E S23 BT".
- A 35" P. Pine bears N12°W, 26.2 ft., dead standing, scribing visible "S14".

Description of monument and accessories | established to perpetuate the original location of this corner:

New BT's:

- A 9 1/2" Fir bears N52 1/2°W, 59.8 ft., scribed T3S R33E S14 BT.
- A 7" D. Fir bears S45 3/4°E, 60.0 ft., scribed T3S R33E S24 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal fence post 4 ft. north of corner.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From USFS Rd. 5427 southeasterly on 5427-090. At 1 mi., road hooks around to the west .2 mi. to its intersection with 5427-093, which is a barricaded road to the west. Follow road 300 ft. west. Corner is 300 ft. south of road.

I hereby certify the above described corner monument and/or accessories was established as described on June 9, 1984.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 13, 1979
B. A. SUTTON
1848

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 7-2-84

Date Filed 7-3-84

By G. LANGLITZ, DEPUTY

File No. 870-84R

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone alongside iron post.

~~Subdivisions, T. 3 S., R. 33 E.,
Willamette Meridian, Oregon~~

~~(Remonumenting corners established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)~~

The cor. of secs. 13, 14, 23, and 24, monumented with the original basalt stone, 20 x 18 x 4 ins., loosely set 1 in. in the ground, in a collar of stone, mkd. with 1 notch on E. and 3 notches on S. edges, from which the remains of the original bearing trees:

A pine, 25 ins. diam., bears N. 57° E., 241 lks. dist., with scribe marks S23 BT visible on open blaze.

A pine, 25 ins. diam., bears S. 58° E., 134 lks. dist., with healed blaze. (Record, 131 lks.)

A pine snag, 10 ins. diam., bears S. 60° W., 35 lks. dist., with scribe marks S13 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 3 S R 33 E
S 14 | S 13
S 23 | S 24
1977

from which a new bearing tree

A fir, 23 ins. diam., bears S. 69½° W., 34½ lks. dist., mkd. T3S R33E S23 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 18 and 19, monumented with the original basalt stone, 16 x 10 x 6 ins., firmly set 6 ins. in the ground, and in a mound of stone, 3 ft. base, 6 ins. high, mkd. ¼ on N. face, from which the remains of the original bearing trees:

A root hole, bears S. 20° W., 46 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks BT visible on open and decayed blaze. (Record, 40 lks.)

A twin pine, 14 ins. diam., bears N. 70° W., 53 lks. dist., no marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T3S33N21

T3S33N03

UNION COUNTY SURVEYOR	
Date Received	3/15/13
Date Filed	3/15/13
By	<i>[Signature]</i> DEPUTY
File No.	361-2013R