


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Index File No. V-23

In 1882, under Glo Contract No. 451, Rufus S. Moore set a post, from which a 5" Pine bears N57°W, 14 lks.; a 5" Pine bears South, 11 lks.



Description of corner evidence found:

No corner evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2"x30" aluminum capped aluminum pipe rising 7", stamped:

New BT's:

An 8" L. Pine bears N70 1/4°E, 34.5 ft., scribed 1/4 S25 BT.
A 5 1/2" L. Pine bears S77°W, 13.9 ft., scribed 1/4 S36 BT

T3S R33E
S25
1/4 ———
S36
1983
LS 1848

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982.

Set metal fence post 5 ft. west of corner.

Compass Declination: 19 1/2°E

Witness: D. Scott

Corner was set at the single-proportioned location. This position fits closely with the terrain call to the marsh to the east as shown in the original GLO notes.

From the south line of S 36 with its intersection with 2110-320, north 400 ft. to an unmarked road that continues northerly & easterly, 1/2 mi. to creek Xing. Take left fork of road 5/8 mi. to Riley Camp cabin. Corner is S19°E, 219 ft. from cabin.

I hereby certify the above described corner monument and/or accessories was established as described on November 28, 1983.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

B. A. Sutton

OREGON
JULY 13, 1979
B. A. SUTTON
1848

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

**UNION COUNTY
SURVEYOR**

Date Received 7-2-84
* OPO-788-278

Date Filed 7-3-84

By G. LANGLITZ DEPUTY

File No. 877-84 R