


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-21

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 16x8x7, from which a 30" Pine bears N32°W, 208 lks. and a 10" Pine bears N85°E, 133 lks.



Description of corner evidence found:

No corner monument found.

Bearing trees found:

- A 32.5" P. Pine bears N29°W, 137.3 ft., scribing visible "1/4 S BT".
- A 22.5" P. Pine bears N85°E, 87.8 ft., scribing visible "1/4 S BT".

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2 1/2"x27" aluminum capped aluminum pipe 6" in ground. Raised mound of earth and stones 4 ft. in diameter at the base, 18" high. Cap rises 4" above mound, stamped:

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal fence post 2 ft. north of corner.


Compass Declination: 19 1/2°E

Witness: N. Petz

T3S
1/4 R33E
S35 S36
1983
LS 1848

From intersection of 2110-220 and 2110-320, go east 300 ft. to corner.

I hereby certify the above described corner monument and/or accessories was established as described on September 13, 1983.



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Date Received <u>7-2-84</u>
Date Filed <u>7-3-84</u>
By <u>G. LANGUTZ DEPUTY</u>
File No. <u>879-84R</u>