


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 16x8x7, from which a 24" Fir bears N35°E, 42 lks. and an 8" Pine bears N65°W, 26 lks.

Index File No. X-25



Description of corner evidence found:

Found stone of proper dimensions, but with no markings.

Bearing trees found:

- A 16" L. Pine bears N65 3/4°W, 17.2 ft., dead standing.
- A 28" Fir bears N35°E, 27.7 ft., scribing visible "1/4 S BT"

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2" aluminum cap on 2 1/2"x30" aluminum pipe rising 12" in mound, stamped:

New BT:

- A 5" D. Fir bears N54 1/4°W, 24.9 ft., scribed 1/4 S36 BT.

T3S
 R33E 1/4 R33 1/2E
 S36
 1983
 RLS 1848

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal fence post 4 ft. north of corner.

Compass Declination: 19 1/2°E
Witness: D. Scott

From the south line of S36 with its intersection with 2110-320, go north 400 ft. to an unmarked road that continues northerly & easterly, 1/2 mi. to creek crossing. Take right fork of road up the hill to the SE 1/4 mi. to a fork. Take the left fork and go northeasterly & go another 1/4 mi. or so to another fork and take the right fork. Go another 1/4 mi. and take a right fork again. Follow road 3/8 mi. more or less to a clearing on left. Go downhill 300 ft. to the corner at the NE corner of the clearing.

I hereby certify the above described corner monument and/or accessories was established as described on November 28, 1983.

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

 OREGON
 JULY 13, 1979
 B. A. SUTTON
 1848

Office of..... County of.....
 State of..... I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....

..... by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
 SURVEYOR
 Date Received 7-2-84
 Date Filed 7-3-84
 By G. LANGUTZ, DEPUTY
 File No. 880-84 R