## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established by Rufus S. Moore under GLO contract number 451 during November, 1881. Corner was recovered by L. Wilkes, survey group #38, in October, 1917. Surveyor's generals notes state: "Intersect the old cor. of secs. 3, 4, 33 and 34, which is a basalt stone, 8x8x7 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, with the exception that the SW bearing tree is now dead. I mark a new tree, as follows:

Index File No. DIAGRAM T2S R34E S33 | S34 S4 | S3 T3S

from cor. A tamarack, 8 ins. diam., bears S37°, 30'W., 29 lks. dist. marked T3SR34E

## Description of corner evidence found:

Found 16x7x7 inch stone in mound of stone, clearly marked with 3 notches on one side from which: A 22" tamarac stump bears S34°W, 18.0 ft. with clear E and T from opened blaze. A 9" lodgepole pine bears N57°E, 17.0 ft. with dim full scribed. Stump hole approximate. Lodgepole is down and rotten.

## Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 20" in the ground and mound of stone around to cap. Placed marked stone alongside. From which by magnetic declination of N20°E:
A 15" fir bears N77°E, 33.9 ft. scribed T2SR34ES34 BT.
A 12" tamarac bears S80°E, 32.3 ft. scribed T3SR34ES3 BT.
A 15" tamarac bears S69°W, 74.2 ft. scribed T3SR34ES4 BT.

T2S R34E S33 | S34 T3S OR PLS 1051 1980

A 9" tamarac bears N44°W, 43.6 ft. scribed T2SR34ES33 BT. Painted blazes red and 6" red band around. Placed 54-3, 54-4s and brass washers stamped PLS 1051 on BTs. Placed 54-2 and 54-4 on steel fence post 5' north and 54-2 on steel fence post 5' east of the corner.

> REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON OCT. 17, 1975 BARBOUR 1 0 5 1

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Dan Rowland Doug Moser

October 20, 1980

Office of County Surveyor County of Union  State of Oregon , I hereby certify that the within instrument was filed in this office
State of, I hereby certify that the within instrument was filed in this office
for record on the 30th day of January
by

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

•	
· ceived	
<b>☆ GPO—798-276</b> Pote Filed	
Ву	<del></del>
File No. 368-84	<u>R</u>

ON COUNTY RVEYOR