


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. ^A X-15

History of original corner establishment:

Corner was originally established by Rufus S. Moore, under GLO contract No. 451, during November, 1881. Surveyor General's notes state: "Set basalt stone 18 X 12 X 10 ins. 12 ins. in the ground for 1/4 sec. corner, marked 1/4 on N. face, from which: A pine 15 ins. in diam, bears S42°W, 47 lks. dist. marked 1/4S BT."



Description of corner evidence found:

Found no trace of corner stone or record BTs. Area has had a lot of camping and wood cutting,

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 25" in the ground and mound of stone around to cap.

From which by magnetic declination of N20°E:

A 24" pine bears N39°W, 131.5 ft. scribed 1/4 S34 BT.

An 18" tamarac bears S45°W, 159.9 ft. scribed 1/4 S3 BT.

Painted blazes red and 6" red band around. Placed 54-3s, 54-4s, and brass washers stamped PLS 1051 on the BTs. Placed 54-2 and 54-4 on a steel fence post 5' west of the corner.

T2S R34E
S34
1/4 —+—
S3
T3S
OR PLS 1051
1980

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Doug Moser
Ron Gilroy

November 4, 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of.....County.....Surveyor..... County of.....Union.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 30th day of.....January....., 1981.

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received 798-276

Date Filed _____

By _____

File No. 369-84 R